








مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 DH-HAC-HFW2401EP	1/3" 4.1Megapixel CMOS 25fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD dual-output OSD Menu Max. IR length 40m, Smart IR IP67, DC12V		4,030,000
2 DH-HAC-HFW2401DP	1/3" 4.1Megapixel CMOS 25fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD dual-output OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		4,310,000
3 DH-HAC-HFW1400RP-VF-IRE6	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm vari-focal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V		5,010,000
4 DH-HAC-HFW1400DP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		3,470,000
5 DH-HAC-HFW1400BP	1/3" 4Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V		3,240,000
6 DH-HAC-HFW1400SP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V		2,820,000
7 DH-HAC-HFW1400TP	1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 25m, Smart IR IP67, DC12V		2,590,000









8	DH-HAC-ME1400B-PIR <b>NEW Product</b>	4MP HDCVI MotionEye Camera 1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V		2,990,000
9	DH-HAC-HFW2231RP-Z-IRE6	1/2.8" 2.1Megapixel CMOS, <b>(Starlight)</b> 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Motorized lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 60m, Smart IR IP67, DC12V		6,740,000
10	DH-HAC-HFW2231EP	1/2.8" 2.1Megapixel CMOS <b>(Starlight)</b> 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 40m, Smart IR IP67, DC12V		4,150,000
11	DH-HAC-HFW2231DP	1/2.8" 2.1Megapixel CMOS <b>(Starlight)</b> 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 80m, Smart IR IP67, DC12V		4,540,000
12	DH-HAC-HFW1220RP-VF-IRE6	1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 60m, Smart IR IP67, DC12V		3,860,000
13	DH-HAC-HFW1220DP	1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 80m, Smart IR IP67, DC12V		2,510,000
14	DH-HAC-HFW1220BP-B-0360B	1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V		2,36,000





15	DH-HAC-HFW1220SP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		2,000,000
16	DH-HAC-HFW1200DP <b>NEW Product</b>	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR IP67, DC12V</p>		2,450,000
17	DH-HAC-HFW1200BP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable 3.6mm fixed lens Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		2,280,000
18	DH-HAC-HFW1200SP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		1,930,000
19	DH-HAC-HFW1200SLP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		1,590,000
20	DH-HAC-HFW1200TP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR , Support OSD Menu Max. IR length 25m, Smart IR IP67, DC12V</p>		1,760,000
21	DH-HAC-HFW1200RMP-0360B <b>Metal Case</b>	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 20m, Smart IR IP67, DC12V</p>		1,670,000
22	DH-HAC-ME1200BP-PIR <b>NEW Product</b>	<p>2MP HDCVI MotionEye Camera 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR 10m/110°detecting range/angle HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, DC12V</p>		2,200,000







23	DH-HAC-HUM1220AP	<p>2MP HDCVI MotionEye Camera            1/2.9" 2Megapixel CMOS            25/30fps@1080P, 25/30/50/60fps@720P            2.8mm fixed lens            HD and SD output switchable            DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR , Support OSD Menu            12m/100°detecting range/angle            Two level(jumper) detection sensitivity adjustable            Built-in tamper switch            DC12V</p>		2,840,000
24	DH-HAC-HUM3201B	<p>1/2.8" 2Megapixel CMOS(<b>Starlight</b>)            25/30fps@1080P, 25/30fps@720P            3.6mm fixed lens            HD and SD output switchable            WDR(120dB), Day/Night(ICR), AWB, AGC, BLC,HLC, 3DNR , Support OSD Menu            DC12V</p>		3,720,000
25	DH-HAC-HFW1100RP-VF	<p>1/2.9" 1Megapixel CMOS            25/30fps@720P            Day/Night(ICR), AWB, AGC, BLC, 2DNR            2.7~12mm vari-focal lens            Max. IR LEDs length 30m, Smart IR            IP67, DC12V</p>		2,080,000
26	DH-HAC-HFW1100SP	<p>1/3" 1Megapixel CMOS            25/30fps@720P            3.6mm fixed lens            HD and SD output switchable            Support OSD Menu            DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR            Max. IR LEDs length 30m, Smart IR            IP67, DC12V</p>		1,340,000
27	DH-HAC-HFW1100SL	<p>1/3" 1Megapixel CMOS            25/30fps@720P            3.6mm fixed lens            HD and SD output switchable            Support OSD Menu            DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR            Max. IR LEDs length 30m, Smart IR            IP67, DC12V</p>		1,110,000
28	DH-HAC-HFW1100RMP-0280B Metal Case	<p>1/2.9" 1Megapixel CMOS            25/30fps@720P            Day/Night(ICR), AWB, AGC, BLC, 2DNR            2.8mm fixed lens            Max. IR LEDs length 20m, Smart IR            IP67, DC12V</p>		1,150,000
29	DH-HAC-HFW1100RMP-0360B Metal Case	<p>1/2.9" 1Megapixel CMOS            25/30fps@720P            Day/Night(ICR), AWB, AGC, BLC, 2DNR            3.6mm fixed lens            Max. IR LEDs length 20m, Smart IR            IP67, DC12V</p>		1,150,000
30	DH-HAC-HFW1100RP	<p>1/3" 1Megapixel CMOS            25/30fps@720P            3.6mm fixed lens            HD and SD output switchable            Support OSD Menu            DWDR, Day/Night(ICR), AWB, AGC, BLC, 2DNR            Max. IR LEDs length 20m, Smart IR            IP67, DC12V</p>		1,020,000



31	DH-HAC-HDW2401EMP	<p>1/3" 4.1Megapixel CMOS 25fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD dual-output OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>		3,890,000
32	DH-HAC-HDBW1400RP-VF	<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 2.7-13.5mm Varifocal lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, IK10, DC12V</p>		4,810,000
33	DH-HAC-HDW1400EMP-A	<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable <b>Built-in Mic</b> OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>		2,930,000
34	DH-HAC-HDW1400EMP	<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67, DC12V</p>		2,800,000
35	DH-HAC-HDW1400MP	<p>1/3" 4.1Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		2,590,000
36	DH-HAC-HDBW2231FP	<p>1/2.8" 2.1Megapixel CMOS <b>(Starlight)</b> 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 20m, Smart IR IP67, IK10, DC12V</p>		4,290,000
37	DH-HAC-HDW2231EMP	<p>1/2.8" 2.1Megapixel CMOS <b>(Starlight)</b> 25/30fps@1080P, 25/30fps@720P 3.6mm Fixed lens WDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNR HD and SD output switchable OSD Menu Max. IR length 50m, Smart IR IP67,DC12V</p>		4,160,000

38	DH-HAC-HDBW1220RP-VF	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 2.7-12mm vari-focal lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, IK10, DC12V</p>		3,580,000
39	DH-HAC-HDW1220EMP-A	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens <b>Built-in Mic</b> HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		2,100,000
40	DH-HAC-HDW1220MP	<p>1/2.9" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,820,000
41	DH-HAC-HDW1200MP	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lens HD and SD output switchable Day/Night(ICR), AWB, AGC, BLC, 2D-DNR , Support OSD Menu Max. IR length 30m, Smart IR IP67, DC12V</p>		1,730,000
42	DH-HAC-HDW1200EMP-A <b>Metal Case</b>	<p>1/2.7" 2Megapixel CMOS 25/30fps@1080P <b>Built-in MIC</b> Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens (6mm optional) Max. IR LEDs length 50m, Smart IR IP67, DC12V</p>		2,040,000
43	DH-HAC-HDW1100MP-0360B	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 30m, Smart IR IP67, DC12V</p>		1,040,000
44	DH-HAC -HDW1100RP-0360B	<p>1/3" 1Megapixel CMOS 25/30fps@720P 3.6mm fixed lens HD and SD output switchable Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC,HLC, 2DNR Max. IR LEDs length 20m, Smart IR IP67, DC12V</p>		1,020,000
45	SD22204I-GC	<p>Powerful 4x optical zoom (2.7mm~11mm) Max. 25/30fps@1080P, 50/60fps@720P resolution WDR, Day/Night (ICR), DNR (2D&amp;3D), Auto iris, Auto focus, AWB, AGC, BLC Max 100°/s pan speed HD &amp; SD Switchable Up to 300 presets, 5 auto scan, 8 tour, 5 pattern IP66, IK10, OSD</p>		7,150,000



46	DH-SD59225I-HC-S2	<p>1/2.8" 2Megapixel Exmor R CMOS <b>(Starlight)</b>            Max 25/30fps @1080P &amp; 20/30/50/60fps @720P Resolution            4.8mm ~ 120mm 25x optical zoom            WDR (120db), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max 400°/s pan speed, 360° endless pan rotation            Control over coaxial cable            1-channel BNC HDCVI/CVBS output (switchable)            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Built-in 2/1 Alarm in/out            1 Audio Input , RS485            IR Distance up to 150m            IP66,OSD</p>		31,850,000
47	SD59230I-HC	<p>2MP 30x Starlight IR PTZ HDCVI Camera            1/2.8" Exmor R CMOS            Max. 25/30fps @1080P(1920x1080) &amp; 20/30/50/60fps @720PResolution            4.5mm~135mm 30x optical zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Max 400°/s pan speed, 360° endless pan rotation            HD and SD switchable            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Audio(in/out) 1 / 1            Built-in 2/1 Alarm in/out            IR Distance up to 150m            IP66,OSD</p>		40,950,000
48	DH-SD49225I-HC	<p>2MP 25x Starlight IR PTZ HDCVI Camera            1/2.8" STARVIS CMOS            Max. 25/30fps @1080P(1920x1080) &amp; 20/30/50/60fps @720P Resolution            4.8mm~120mm 25x optical zoom            WDR(120dB), Day/Night(ICR), Ultra DNR, HLC, BLC, Auto iris, Auto focus            Max 400°/s pan speed, 360° endless pan rotation            HD and SD switchable            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            2/1 Alarm In/Out            1CH Audio In            RS485            IR Distance up to 100m            IP66,OSD</p>		22,100,000
49	DHI-XVR5104HS-S2	<p>4CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder            4M-N/1080P@15fps , 1080N/720P@25fps            H.264+/H.264 dual-stream video compression            4CH: 1/4 Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)]            Support Smart Search and Intelligent Video System            1 Audio Input / 1 Audio Output            1 SATA Port , Up to 8 TB            HDMI , VGA ,simultaneous video Output            RS485 for PTZ support            2*USB 2.0            10/100 Mbps LAN Interface            P2P Support</p>		4,400,000
50	DHI-XVR5104HS-4M	<p>4CH Penta-brid 4MP Non-real Time , 1080P Real-Time Recorder            H.264+/H.264 dual-stream video compression            4CH Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 5 Megapixel(24 Mbps)]            Support Smart Search and Intelligent Video System            1/1 Audio In/Out            1 SATA Port , Up to 8 TB            1*HDMI(2K) ,1* VGA ,simultaneous video Output            RS485 for PTZ support            2*USB 2.0            10/100 Mbps LAN Interface            P2P Support</p>		6,140,000

51	DH-HCVR7104H-4M	<p>4CH 4Mp None-real time, 1080P Real-Time CVI Recorder  H.264+/H.264 Dual-stream video compression  Tribrid(IP+CVI+Analogue) N+M [4+2 IP up to 5 Megapixel(24 Mbps)]  1/4/6 Display  1/4 CH Playback  1 Audio Input/ 1 Audio Output  1 SATA Port , Up to 6 TB  1*HDMI(4K),1* VGA simultaneous video Output  RS485 for PTZ support  2 USB Ports (1 USB 2.0 , 1 USB 3.0)  1 LAN Interface(1000M)  DC12V/2A Power Supply  P2P Support</p>		7,150,000
52	DHI-XVR5108HS-S2 NEW Product 	<p>8CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder  4M-N/1080P@15fps , 1080N/720P@25fps  H.264+/H.264 dual-stream video compression  8CH:1/4/9 Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 5 Megapixel(48 Mbps)]  Support Smart Search and Intelligent Video System  1 Audio Input / 1 Audio Output  1 SATA Port , Up to 8 TB  HDMI , VGA ,simultaneous video Output  RS485 for PTZ support  2*USB 2.0  10/100 Mbps LAN Interface  P2P Support</p>		7,280,000
53	DHI-XVR5108H-4KL 	<p>8CH Penta-brid 4K Recorder  4K@7fps, 4MP@15fp , 1080P/720P@25fps  H.264+/H.264 dual-stream video compression  8CH Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+4 IP up to 8 Megapixel(48 Mbps)]  Support Smart Search and Intelligent Video System  1/1 Audio In/Out  1 SATA Port , Up to 8 TB  1*HDMI(4K) , 1*VGA ,simultaneous video Output  RS485 for PTZ support  2*USB 2.0  1*10/100/1000 Mbps LAN Interface  P2P Support</p>		9,360,000
54	DH-HCVR7108H-4M	<p>8CH 4Mp None-real time, 1080P Real-Time CVI Recorder  H.264+/H.264 Dual-stream video compression  Tribrid(IP+CVI+Analogue) N+M [8+4 IP up to 5 Megapixel(48 Mbps)]  1/4/8/9/16 Display  1/4/9CH Playback  1 Audio Input/ 1 Audio Output  1 SATA Port , Up to 6 TB  1*HDMI(4K),1*VGA simultaneous video Output  RS485 for PTZ support  2 USB Ports (1 USB 2.0 , 1 USB 3.0)  1 LAN Interface(1000M)  DC12V/2A Power Supply  P2P Support</p>		10,270,000
55	DH-HCVR7208AN-4M	<p>8CH 4Mp None-real time, 1080P Real-Time CVI Recorder  H.264+/H.264 Dual-stream video compression  Tribrid(IP+CVI+Analogue) N+M [8+4 IP up to 5 Megapixel(48 Mbps)]  1/4/8/9/16 Display  1/4/9CH Playback  1 Audio Input/ 1 Audio Output  2 SATA Port , Up to 12 TB  1*HDMI(4K),1*VGA simultaneous video Output  RS485 for PTZ support  2 USB Ports (1 USB 2.0 , 1 USB 3.0)  1 LAN Interface(1000M)  DC12V/4A Power Supply  P2P Support</p>		13,520,000



56 DH-XVR5216AN-S2	NEW Product 	<p>16CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder            4M-N/1080P@15fps , 1080N/720P@25fps            H.264+/H.264 dual-stream video compression            1/4/9/16CH Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96 Mbps)]            Support Smart Search and Intelligent Video System            1/1 Audio In/Out            2 SATA Port , Up to 16 TB            HDMI , VGA ,simultaneous video Output            RS485 for PTZ support            2 USB Ports (1 USB 2.0 , 1 USB 3.0)            10/100/1000 Mbps LAN Interface            P2P Support</p>		14,170,000
57 DHI-XVR5216AN-4KL		<p>16CH Penta-brid 4K Recorder            4K@7fps, 4MP@15fp , 1080P/720P@25fps            H.264+/H.264 dual-stream video compression            16CH Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 8 Megapixel(96 Mbps)]            Support Smart Search and Intelligent Video System            1/1 Audio In/Out            2 SATA Port , Up to 16 TB            1*HDMI(4K) , 1*VGA ,simultaneous video Output            RS485 for PTZ support            2*USB 2.0            1*10/100/1000 Mbps LAN Interface            P2P Support</p>		17,940,000
58 DH-HCVR7216AN-4M		<p>16CH 4Mp None-real time, 1080P Real-Time CVI Recorder            H.264+/H.264 Dual-stream video compression            Tribrid(IP+CVI+Analogue) N+M [16+8 IP up to 5 Megapixel(96 Mbps)]            1/4/8/9/16/25 Display            1/4/9/16CH Playback            1 Audio Input/ 1 Audio Output            2 SATA Port , Up to 12 TB            1*HDMI(4K),1*VGA simultaneous video Output            RS485 for PTZ support            2 USB Ports (1 USB 2.0 , 1 USB 3.0)            1 LAN Interface(1000M)            DC12V/5A Power Supply            P2P Support</p>		18,720,000
59 DH-XVR5416L		<p>16CH Penta-brid 1080N/720P Real-Time,1080P None-Real time Recorder            H.264+/H.264 dual-stream video compression            1/4/9/16CH Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96Mbps)]            4 Audio IN / 1 Audio Out            16 Alarm IN / 6 Alarm Out            4 SATA Port , Up to 6 TB            1 e-SATA            2*HDMI , VGA , TV simultaneous video Output            RS485 , RS 232            2 USB 3.0, 1 USB 2.0            10/100/1000 Mbps LAN Interface            P2P Support</p>		25,740,000
60 DH-XVR7416L		<p>16CH Penta-brid 1080P Real-Time Recorder            H.264+/H.264 dual-stream video compression            1/4/9/16CH Playback            Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+8 IP up to 5 Megapixel(96Mbps)]            4 Audio IN / 1 Audio Out            16 Alarm IN / 6 Alarm Out            4 SATA Port , Up to 6 TB            1 e-SATA            2*HDMI , VGA , TV simultaneous video Output            RS485 , RS 232            2 USB 3.0, 1 USB 2.0            10/100/1000 Mbps LAN Interface            P2P Support</p>		35,100,000

61	DH-HCVR8816S-S3	<p>All channel 1080P realtime recording  Support HDCVI/AHD/Analog/IP Video input  H.264 dual-stream video compression  16 channel synchronous realtime playback  Tribrid (IP+CVI+Analogue)N+M[16+48 up to 12Megapixel(384Mbps)]  16 Audio Input , 1 Audio Output  16*Alarm Input , 6*Relay Output  8 SATA ports, up to 64TB, 1 eSATA  2 HDMI(HDMI1 up to 4K), 1 VGA, 1 TV  HDMI 1/VGA simultaneous video output,HDMI2/VGA(HDMI1) independent video output  RS485 , PTZ Support  4 ports (2 Rear USB3.0, 2 Front USB2.0)  2*10/100/1000 Mbps LAN Interface  IVS: Tripwire, Intrusion, Abandoned/Missing, Scene Change, Face Detection, People Counting,  Smart Tracking  P2P Support</p>		Call
62	DH-XVR5232AN-S2	<p>32CH Penta-brid 4M-N/1080P Non-real Time , 1080N/720P Real-Time Recorder  4M-N/1080P@15fps , 1080N/720P@25fps  H.264+/H.264 dual-stream video compression  16CH:1/4/9/16CH Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [32 IP up to 5 Megapixel(128 Mbps)]  Support Smart Search and Intelligent Video System  1/1 Audio In/Out  2 SATA Port , Up to 16 TB  HDMI , VGA , 1TV video Output  RS485 for PTZ support  2 USB Ports (1 USB 2.0 , 1 USB 3.0)  10/100/1000 Mbps LAN Interface  P2P Support</p>		24,310,000
63	DH-XVR5432L	<p>32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder  H.264+/H.264 dual-stream video compression  1/4/9/16CH Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)]  4 Audio IN / 1 Audio Out  16 Alarm IN / 6 Alarm Out  4 SATA Port , Up to 8 TB  1 e-SATA Port  2 HDMI, 1 VGA, 1 TV  RS485 , RS232, RS422  2 USB 3.0, 1 USB 2.0  10/100/1000 Mbps LAN Interface  Smart Search and Intelligent Video System  P2P Support</p>		41,600,000
64	DH-XVR5832S	<p>32CH Penta-brid 1080P None-Real time, 1080N/720P Real-Time Recorder  H.264+/H.264 dual-stream video compression  1/4/9/16CH Playback  Pentabrid (IP+CVI+AHD+TVI+CVBS)[32 IP up to 5 Megapixel(128Mbps)]  16 Audio IN / 1 Audio Out  16 Alarm IN / 6 Alarm Out  8 SATA Port , Up to 8 TB  1 e-SATA Port  2 HDMI, 1 VGA, 1 TV  RS485 , RS232, RS422  2 USB 3.0, 2 USB 2.0  10/100/1000 Mbps LAN Interface  Smart Search and Intelligent Video System  P2P Support</p>		50,700,000
65	PFT2100	<p>HDMI-HDCVI Converter  *Input HDMI video signal, self-adaptive output HDCVI signal  *HDMI support mode, 1024*768@60Hz, 1280*720@50/60Hz,  1280*1024@60Hz,1600*1200@60Hz, 1920*1080@50/60Hz  *HDCVI output format, 720P/50, 720P/60, 1080P/25, 1080P/30  *Output Cable Length 1080P: 75-5 coaxial cable support 300m/720P: 75-5 coaxial cable  support 500m  *Power:DC12V</p>		3,580,000

66	TP2105	<p>HDCVI Video Converter real time non-compression transmission *Input: 1*HDCVI (BNC) *Output: 1*HDCVI (BNC), 1*CVBS (BNC), 1*HDMI, 1*VGA *1080p/720p: 75-5 coaxial support 100m Input Transmission Distance *1080p/720p: 75-5 coaxial support 100m HDCVI Output Transmission Distance *Support 2 dial switches and indicate 4 Baud rate: 2400b/s, 4800b/s, 9600b/s and 115200b/s *RS485</p>		3,770,000
67	PFM801	<p>*1 Channel HDCVI Transmission Signal *720P, 400M(max); 1080P, 200M(max)Transmission Distance *Input voltage DC24-36V, can provide DC12V8W(max) power supply to remote camera *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal and 1-ch DC power *Excellent anti-thunder, anti-static and anti-interference capabilities *Compatible with HDCVI/TVI/AHD format</p>		510,000
68	DH-PFM900-E	<p>4" IPS screen and QWERTY flip keyboard with 45keys Support H.264/H.265 HD decoding protocol Support IP,HDCVI/AHD/TVI/CVBS Support IP configuration via Onvif protocol Support audio and RS485 control Support TDR network cable test and digital multi-meter function Support PoE+, DC12V/2A power out; Replaceable 7.4V/22.2Wh polymer lithium ion battery , which can last 8 hours for normal use; Compatible with more than 30 PTZ protocols(Pelco-D/P, Samsung, Panasonic, Lilin, Yaan,...) Dual LED flashlight</p>		34,450,000
69	DH-PFM905-E	<p>4" IPS display, 800*480 resolution, 16.7M colors Support HDCVI/AHD/TVI/CVBS Support RS485 PTZ control Support audio test and digital multi-meter function Support DC12V/1A power out Dual LED torch light Replaceable 7.4V/10.4Wh polymer lithium battery , which can last 5 hours for normal use</p>		16,900,000

fanavarancctv@  
ID: @FTNCCTV

www.hikpersian.ir  
شرکت فناوری تصویر نوین  
021-66754022

