

مدل ردیف	مشخصات فنی	IP CAMERA	تصویر	قیمت (ریال)
1 DH-PSD81602-A360	<p>8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out 7/2 channel Alarm In/Out RS485 Micro SD memory, IP67, IK10</p>			Call
2 DH-PSD8802-A180	<p>4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out 7/2 channel Alarm In/Out RS485 Micro SD memory, IP67, IK10</p>			Call
3 IPC-PFW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function  Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/2 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10,PoE+</p>			Call
4 IPC-PFW8601-A180	<p>3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832 3.6mm fixed lens Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function  Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out 2/1 channel Alarm In/Out Max. IR LEDs length 30m Micro SD memory, IP67, IK10,PoE+</p>			Call


ردیف	مدل	مشخصات فنی	تصویر	قیمت (ریال)
5	DH-IPC-PDBW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Dome Camera            Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS            H.265+/H.265/H.264+/H.264            Max 25fps@4096x1800            3.0mm fixed lens            Support 180-degree panoramic view            DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC            Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ            1/1 channel Audio In/Out            2/1 channel Alarm In/Out            Max. IR LEDs length 30m            Micro SD memory, IP67, IK10,PoE+</p>		Call
6	IPC-HFW5830E-Z	<p>1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS            H.265+/H.265/H.264+/H.264 dual-stream encoding            15fps@4K(3840x2160),25/30fps@3Mp(2304x1296)            2.7mm ~12mm motorized lens            Max. Aperture F1.6            DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC            Micro SD card memory , 128 GB            1*Audio in/1*Audio Out            2*Alarm In/1* Alarm Out            Max. IR LEDs Length 50m            IP67,IK10, PoE            Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		Call
7	IPC-HFW4631EP-SE	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS            H. 265+ &amp; H.265 &amp; H.264+ &amp; H.264 triple-stream encoding            20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520)            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC            3.6mm fixed lens            Max. IR LEDs Length 40m            Micro SD card memory , 128 GB            IP67, PoE            Smart Detection (Tripwire Intrusion  Object Abandoned/Missing  Face)</p>		9,880,000
8	DH-IPC-HFW5431EP-Z-H	<p>1/3" 4Megapixel progressive scan CMOS            H.265+/H.265/H.264+/H.264 &amp; MJPEG triple-stream encoding            Max 20fps@4Mp(2560x1440),25/30fps@3M(2304x1296)            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC            2.7mm ~12mm motorized lens            Max. IR LEDs Length 50m            IP67, PoE            Micro SD card memory , 128 GB            Audio in/Out            Alarm In/Out            Smart Detection (Tripwire Intrusion   Scene Change   Face)</p>		10,870,000
9	DH-IPC-HFW4830EP-S	<p>1/2.5" 8Megapixel progressive scan CMOS            H.265+&amp;H.265&amp;H.264&amp;MJPEG triple-stream encoding            15fps@4K(3840x2160),25/30fps@3Mp(2304x1296)            DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC            4mm fixed lens            Max. IR LEDs Length 40m            Micro SD card memory , 128 GB            IP67, PoE            Smart Detection (Tripwire Intrusion   Scene Change   Face)</p>		11,500,000
10	DH-IPC-HFW4431DP-BAS-H <b>Eco-Savvy Lite</b>	<p>1/3" 4Megapixel progressive scan CMOS            3.6mm fixed lens            Max 20fps@4M(2592x1520) &amp; 25/30fps@3M(2304x1296)            H.265+/H.265/H.264+/H.264 &amp; MJPEG triple stream encoding            WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC            Smart Detection supported            Face Detection,Tripwire, Intrusion, Object Abandoned/Missing            1/1 Alarm in/out, 1/1 audio in/out            Max. IR LEDs Length 80m            Mirco SD card 128GB            IP67, PoE</p>		6,350,000








11	DH-IPC-HFW4431BP-BAS-H <b>Eco-Savvy Lite</b>	1/3" 4Megapixel progressive scan CMOS 3.6mm fixed lens Max 20fps@4M(2592×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 & MJPEG triple stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported Face Detection, Tripwire, Intrusion, Object Abandoned/Missing 1/1 Alarm in/out, 1/1 audio in/out Max. IR LEDs Length 50m Mirco SD card 128GB IP67, PoE		6,000,000
12	DH-IPC-HFW1431SP	1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m IP67, PoE		5,920,000
13	DH-IPC-HFW4231EP-S <b>ECO-SAVVY 3.0</b>	1/2.8" 2Megapixel progressive scan STARVIS™ CMOS(Starlight) 3.6mm fixed lens 50/60fps@1080P(1920×1080) H.265+/H.265/H.264+/H.264 triple-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported: Face Detection, Tripwire, Intrusion, Object Abandoned/Missing Max. IR LEDs Length 40m Mirco SD card 128GB IP67, PoE		7,930,000
14	DH-IPC-HFW2431RP-ZS-IRE6	1/3" 4Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB Max IR LEDs Length 60m IP67, PoE		10,150,000
15	DH-IPC-HFW2431RP-VFS-IRE6	1/3" 4Megapixel progressive CMOS 2.7~13.5mm varifocal lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB Max IR LEDs Length 60m IP67, PoE		8,730,000
16	DH-IPC--HFW2231RP-VFS-IRE6	1/2.8" 2Megapixel progressive Starvis CMOS(Starlight) 2.7~13.5mm varifocal lens 25/30fps@2M(1920×1080) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB Max IR LEDs Length 60m IP67, PoE		8,190,000
17	DH-IPC--HFW2231RP-ZS-IRE6	1/2.8" 2Megapixel progressive Starvis CMOS(Starlight) 2.7~13.5mm Motorized lens 25/30fps@2M(1920×1080) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Mirco SD card 128GB Max IR LEDs Length 60m IP67, PoE		9,700,000





18	DH-IPC-HFW1420SP	<p>1/3" 4Megapixel progressive scan CMOS H.264&amp;MJPEG dual-stream encoding Max 20fps@4M(2688×1520)&amp;25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p>		Discontinue
19	DH-IPC-HFW1320SP-0360B	<p>1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding Max 20fps@3M(2048× 1536)&amp;25/30fps@1080P(1920× 1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p>		4,680,000
20	DH-IPC-HFW1230SP	<p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p>		3,970,000
21	HDBW-5830EP-Z	<p>1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) 2.7mm ~12mm motorized lens Max. Aperture F1.6 DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card memory , 128 GB 1*Audio in/1*Audio Out 2*Alarm In/1* Alarm Out Max. IR LEDs Length 50m IP67,IK10, PoE Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		Call
22	DH-IPC-HDBW5431EP-Z-H	<p>1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 &amp; MJPEG triple-stream encoding Max 20fps@4Mp(2560×1440),25/30fps@3M(2304x1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens Max. IR LEDs Length 50m IP67,IK10, PoE Micro SD card memory , 128 GB Audio in/Out Alarm In/Out Smart Detection (Tripwire Intrusion   Scene Change   Face)</p>		10,870,000
23	DH-IPC-HDBW4830EP-AS	<p>1/2.5" 4K progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens Max. IR LEDs Length 30m Alarm in/out Audio in/out Micro SD card memory , 128 GB IP67,IK10, PoE Smart Detection (Tripwire Intrusion Scene Change Object Abandoned/Missing  Face)</p>		11,180,000
24	DH-IPC-HDW4830EMP-AS	<p>1/2.5" 4K progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160),25/30fps@3Mp(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens Max. IR LEDs Length 50m Built-in Mic Micro SD card memory , 128 GB IP67,PoE Smart Detection (Tripwire Intrusion Scene Change Object Abandoned/Missing  Face)</p>		11,180,000





25	DH-IPC-HDW4431EP-AS-H <b>Eco-Savvy Lite</b>	<p>1/3" 4Megapixel progressive scan CMOS 3.6mm fixed lens Max 20fps@4M(2592×1520) &amp; 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 &amp; MJPEG triple stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported Face Detection, Tripwire, Intrusion, Object Abandoned/Missing Built-in Mic Max. IR LEDs Length 50m Micro SD card 128GB IP67, PoE</p>		6,000,000
26	DH-IPC-HDBW2431RP-ZAS	<p>1/3" 4Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Micro SD card 128GB Max IR LEDs Length 50m IP67, IK10, PoE</p>		10,150,000
27	DH-IPC-HDBW2421RP-ZS	<p>1/3" 4Megapixel progressive CMOS 2.7~12mm Motorized lens H.264+ &amp; H.264 dual-stream encoding 20fps@4M(2688×1520) &amp; 25/30fps@2M(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card slot, up to 128GB Max IR LEDs Length 30m IP67, IK10, PoE</p>		8,970,000
28	DH-IPC-HDBW2421RP-VFS	<p>1/3" 4Megapixel progressive CMOS 2.7~12mm varifocal lens 20fps@4M(2688×1520) &amp; 25/30fps@2M(2304×1296) H.264+ &amp; H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card 128GB Max IR LEDs Length 30m IP67, IK10, PoE</p>		7,670,000
29	DH-IPC-HDBW2431RP-VFS	<p>1/3" 4Megapixel progressive CMOS 2.7~13.5mm varifocal lens 20fps@4M(2688×1520)&amp;25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Micro SD card 128GB Max IR LEDs Length 50m IP67, IK10, PoE</p>		8,780,000
30	DH-IPC-HDBW1431EP	<p>1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m IP67, IK10, PoE</p>		6,050,000
31	DH-IPC-HDW1431SP	<p>1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 20fps@4M(2688×1520) &amp; 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m IP67, PoE</p>		5,920,000

32	DH-IPC-HDPW1420FP-AS	<p>1/3" 4Megapixel progressive scan CMOS H.264 &amp; MJPEG dual codec Max 20fps@4M(2688*1520), 25/30fps@3M(2304*1296) Smart Detection supported DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Built-in Mic Mirco SD card 128GB Max. IR LEDs Length 20m IP66,PoE</p>		Discontinue
33	DH-IPC-HDW1420SP	<p>1/3" 4Megapixel progressive scan CMOS H.264&amp;MJPEG dual-stream encoding Max 20fps@4M(2688x1520)&amp;25/30fps@3M(2304x1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p>		Discontinue
34	DH-IPC-HDBW1320EP-AS-0360B	<p>1/3" 3Megapixel progressive scan CMOS H.264+/H/264 dual-stream encoding Max 20fps@3M(2048x1536) (2304x1296)&amp;25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m Micro SD card Memory , 128 GB Audio In/Out IP67, IK10, PoE</p>		5,070,000
35	DH-IPC-HDW1230SP	<p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens Max. IR LEDs Length 30m IP67, PoE</p>		3,970,000
36	DH-IPC-HDBW1230EP	<p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920x1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens Max. IR LEDs Length 30m IP67, IK10, PoE</p>		4,100,000
37	DH-IPC-HDBW8231EP-Z	<p>1/2.8" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding 50/60fps@1080P(1920x1080) WDR(140dB), SSA, Day/Night(ICR), 3DNR,AWB,AGC,BLC 2.7mm ~12mm motorized lens Max. IR LEDs Length 50m Micro SD card memory , 128 GB Audio In/Out Alarm In/Out Support EIS ,Defog Support <b>People Counting, Heat Map</b> IP67, IK10, PoE Smart Detection (Tripwire   Intrusion   Scene Change   Object Abandoned/Missing   Face)</p>		Call
38	DH-SD29204T-GN	<p>1/2.7" 2MP CMOS Sensor H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 2.7mm ~ 11mm , 4x Optical Zoom Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic IR Distance up to 30m support POE Smart Detection (Tripwire   Intrusion   Scene Change   Face   Abandoned-Missing Object)</p>		11,600,000

39 DH-SD6CE230U-HNI <b>NEW Product</b>	<p>1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out Audio 1/1 in/out 1*Video output RS485 IR Distance up to 200m PoE+ IP67 IK10</p>		51,350,000
40 DH-SD6CE225U-HNI <b>NEW Product</b>	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P 4.8mm~120mm 25x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC Support Defog, ROI, EIS Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output Rs485 Alarm 7/2 in/out Audio 1/1 in/out IR Distance up to 200m PoE+, IP67, IK10</p>		38,350,000
41 DH-SD49225T-HN	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Support Defog IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 2/1 in/out Audio 1/1 in/out Support PoE+ IR Distance up to 100m IP66</p>		25,040,000
42 DH-SD65F230F-HNI <b>Super Starligh</b>	<p>1/1.9" 2MP CMOS Sensor <b>(Super Starlight)</b> H.264 / MJPEG Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P 6mm~180mm Powerful 30x optical zoom Max 300°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out Audio 1/1 in/out 1 video output RS485 IR Distance up to 100m Support PoE+ IP66,IK10</p>		CAII


43	DH-SD59225U-HNI	<p>2MP 25x <b>Starlight</b> IR PTZ Network Camera            1/2.8" Exmor R CMOS            H.265+/H.265/H.264+/H.264 Encoding            Max. 50/60fps@1080P, 25/30/50/60fps@720P            4.8mm~120mm 25x optical zoom            Max 400°/s pan speed, 360° endless pan rotation            WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection)            Support Defog and EIS            Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan            Built-in 2/1 Alarm in/out            Audio 1/1 in/out            Support PoE+            IR Distance up to 150m            IP66 OSD</p>		34,780,000
44	DH-SD59230U-HNI	<p>2MP 30x <b>Starlight</b> IR PTZ Network Camera            1/2.8" Exmor R CMOS            H.265+/H.265/H.264+/H.264 Encoding            Max. 50/60fps@1080P, 25/30/50/60fps@720P            4.5mm~135mm 30x optical zoom            Max 400°/s pan speed, 360° endless pan rotation            WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            Auto-tracking and IVS(Tripwire, Intrusion, Abandoned/Missing, Face Detection)            Support Defog and EIS            Up to 300 presets, 8 tour, 5 pattern, Auto scan, Auto Pan            Built-in 2/1 Alarm in/out            Audio 1/1 in/out            Support PoE+            IR Distance up to 150m            IP66, OSD</p>		46,800,000
45	DH-SD59430U-HNI	<p>1/3" CMOS Sensor            H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate transmission            Max. 25/30fps@4M(2592x1520) &amp; 50/60fps @1080P resolution            WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            4.5mm ~ 135.0mm , 30x Optical Zoom            Max 400°/s pan speed, 360° endless pan rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Micro SD card memory , 64 GB            Audio In/Out            Alarm In/Out            IP66, POE+            IR Distance up to 100m(AC24V)/ 80m(DC12V)            Smart Detection (Tripwire Intrusion   Scene Change   Face  Anandoned-Missing Object)</p>		53,300,000
46	DH-SD60230T-HN	<p>1/2.8" 2Mp CMOS Sensor            H.264+/H.264 Encoding, Ultra-low bit rate transmission            Max. 30fps@1080P(2592x1520) &amp; 60fps @720P resolution            DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus            4.5mm ~ 135.0mm , 30x Optical Zoom            Max 600°/s pan speed, 360° endless pan rotation            Up to 300 presets, 5 auto scan, 8 tour, 5 pattern            Micro SD card memory , 64 GB            Audio In/Out            Alarm In/Out            IP67, IK10, POE+            Smart Detection (Tripwire Intrusion   Scene Change   Face  Anandoned-Missing Object)</p>		call
47	DH-NVR2104HS-S2	<p>4 channel IP camera input            4 channel Live Preview            H.264+/H.264 decoding            Max 80Mbps incoming bandwidth            Up to 6Mp resolution preview &amp; playback            HDMI/VGA simultaneous video output            Support 1 SATA HDD up to 6TB, 2 USB2.0            100 Mbps Network Card            P2P support</p>		2,470,000
48	DH-NVR2104HS-P-S2	<p>4 channel IP camera input            4 channel Live Preview            H.264+/H.264 decoding            Max 80Mbps incoming bandwidth            Up to 6Mp resolution preview&amp;playback            HDMI/VGA simultaneous video output            Support 1 SATA HDD up to 6TB, 2 USB2.0            100 Mbps Network Card            4 POE Port            P2P support</p>		4,810,000





ردیف	مدل	مشخصات فني	تصوير	قيمت (ريال)
49	DH-NVR2108HS-S2	<p>8 channel IP camera input 4 channel Live Preview H.264+/H.264 decoding Max 80Mbps incoming bandwidth Up to 6Mp resolution preview &amp; playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support</p>		3,120,000
50	DH-NVR-2108HS-8P	<p>8 channel IP camera input 8 channel Live Preview H.264+/H.264 decoding Max 80Mbps incoming bandwidth Up to 6Mp resolution preview&amp;playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card 8 POE Port P2P support</p>		7,150,000
51	DH-NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support</p>		7,720,000
52	DH-NVR4116HS-4KS2	<p>16 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card P2P support</p>		8,710,000
53	DH-NVR4216-4KS2	<p>16 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card P2P support</p>		12,150,000
54	DH-NVR4232-4KS2	<p>32 channel IP camera input 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card P2P support</p>		13,450,000


55	DH-NVR5232-4KS2	<p>32 channel IP camera input            32 channel Live Preview            Up to 12Mp resolution preview&amp;playback            H.265/H.264/MJPEG dual codec decoding            Max 320Mbps incoming bandwidth            Record Rate 320 Mbps            Max 16ch@1080P H.265/H.264 decoding            HDMI/VGA simultaneous video output            16 channel playback            Support 2 SATA HDDs up to 12TB, 2 USB(1 USB3.0)            1000 Mbps Network Card            RS232            4 Alarm Input, 2 Relay Output            Support P2P</p>		21,740,000
56	DH-NVR4432-4KS2	<p>32 channel IP camera input            16 channel Live Preview            H.265/H.264 codec decoding            Max 200Mbps incoming bandwidth            Up to 8MP Resolution for Preview and Playback            HDMI/VGA simultaneous video output            Support 4 SATA HDD up to 6TB            2 USB Ports (1 USB2.0, 1 USB3.0)            16 Alarm Input, 4 Relay Output            RS232 , RS485            2*10/100/1000Mbps Mbps Network Card            P2P support</p>		18,590,000
57	DH-NVR5432-4KS2	<p>32 channel IPC input            32 channel Live Preview            H.265/H.264/MJPEG/MPEG4 codec decoding            Max 320Mbps incoming bandwidth            Up to 12Mp resolution preview&amp;playback            Max 16ch@1080P H.265/H.264 decoding            2HDMI/VGA simultaneous video output            Support 4 SATA HDDs up to 24TB, 3 USB(1 USB3.0, 2USB2.0)            2*1000 Mbps Network Card            RS232            16 Alarm In , 6 Relay Output            P2P Support</p>		32,180,000
58	DH-NVR5464-4KS2	<p>64 channel IPC input            32 Channel Live Preview            H.265/H.264/MJPEG/MPEG4 codec decoding            Max 320Mbps incoming bandwidth            Up to 12Mp resolution preview&amp;playback            Max 16ch@1080P   4ch@4K H.265/ H.264 Playback            2HDMI/VGA simultaneous video output            Support 4 SATA HDDs up to 24TB, 3 USB(1 USB3.0, 2USB2.0)            2*1000 Mbps Network Card            RS232            P2P Support</p>		38,900,000
59	DH-NVR4832-4KS2	<p>32 channel IP camera input            16 channel Live Preview            H.265/H.264 codec decoding            Max 200Mbps incoming bandwidth            Up to 8MP Resolution for Preview and Playback            HDMI/VGA simultaneous video output            Support 8 SATA HDD up to 6TB            3 USB Ports (2 USB2.0, 1 USB3.0)            16 Alarm Input, 4 Relay Output            RS232 , RS485            2*10/100/1000Mbps Mbps Network Card            P2P support</p>		32,180,000


60	DH-NVR5832-4KS2	<p>32 channel IPC input 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&amp;playback Max 16ch@1080P   4ch@4K H.265   H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card RS232 16 Alarm In , 6 Relay Output P2P Support Raid 0/1/5/6/10</p>		44,050,000
61	DH-NVR5864-4KS2	<p>64 channel IPC input 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&amp;playback Max 16ch@1080P   4ch@4K H.265   H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 3 USB(1 USB3.0, 2USB2.0) 2*1000 Mbps Network Card RS232 16 Alarm In , 6 Relay Output P2P Support Raid 0/1/5/6/10</p>		50,700,000
62	DH-NVR608-32-4KS2	<p>Intel Dual-core Processor 32 channel IPC input 32 Channel Live Preview: (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&amp;playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card RS232 , RS485 16 Alarm In , 8 Relay Output</p>		45,480,000
63	DH-NVR608-64-4KS2	<p>Intel Quad-core Processor 64 channel IPC input 32 Channel Live Preview: (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview &amp; playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card RS232 , RS485 16 Alarm In , 8 Relay Output</p>		78,065,000
64	DH-ESS1508C	<p>2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read &gt;64MB/s, write &gt;64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection</p>		18,200,000

65	DH-PFS3006-4ET-60	<p>4-Port Fast Ethernet PoE Switch                      Layer two commercial switch                      2*10/100 Mbps Uplink ports                      4*10/100 Mbps PoE ports                      Port1≤60W, Port2-4≤30W, Total≤60W                      Support IEEE802.3af, IEEE802.3at(PoE+) ,Hi PoE                      1.8Gbps Switching Capacity                      890Kpps Mpps Packet Forwarding Rate                      768Kb Packet Buffer Memory                      MAC atable size is 2K                      Supports DC 48-57V power supply</p>		2,780,000
----	-------------------	--	---	-----------

66	DH-PFS3010-8ET-96	<p>8-Port Fast Ethernet PoE Switch                      Layer two commercial switch                      2*10/100/1000 Mbps Ports                      8*10/100 Mbps PoE Ports                      Port1≤60W, Port2-8≤30W, Total≤96W                      Support IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE                      5.6Gbps Switching Capacity                      4.17 MppsPacket Forwarding Rate                      4Mb Packet Buffer Memory                      MAC Table Size is 16K                      Supports DC 48-57V power supply</p>		4,780,000
----	-------------------	---	---	-----------

67	DH-PFS3110-8P-96	<p>Two-layer industrial PoE switch                      1*1000 Base-X                      1*10/100/1000 Base-T                      8*10/100 Base-T (PoE power supply)                      Each POE power ≤30W, Total≤96W                      Support IEEE802.3af, IEEE802.3at standard                      7.6G Switching Capacity                      4.17 MppsPacket Forwarding Rate                      1Mb Packet Buffer Memory                      MAC auto study and aging, MAC address list capacity is 8K                      Industrial wide temperature design</p>		5,720,000
----	------------------	---	---	-----------

68	DH-PFS4218-16ET-190	<p>Layer 2 management PoE switch                      2*10/100/1000 Base-T (Combo port)                      2*1000 Base-X (Combo port)                      16*10/100 Base-T (PoE power supply)                      Port1/2 support Hi-PoE (60W), PoE+, PoE                      Each power ≤30W, Total≤190W                      Support IEEE802.3af, IEEE802.3at, Hi-PoE                      250 meters long distance PoE transmission                      Support spanning tree protocol STP/RSTP                      Support Vlan:VLAN/802.1Q Standard Vlan                      8.8G Switching Capacity                      5.36 Mpps Packet Forwarding Rate                      Network Management by WEB(http and https protocol)</p>		16,020,000
----	---------------------	---	---	------------

69	DH-PFS4218-16ET-240	<p>Layer 2 management PoE switch                      2*10/100/1000 Base-T (Combo port)                      2*1000 Base-X (Combo port)                      16*10/100 Base-T (PoE power supply)                      Port1/2 support Hi-PoE (60W), PoE+, PoE                      Each power ≤30W, Total≤240W                      Support IEEE802.3af, IEEE802.3at, Hi-PoE                      250 meters long distance PoE transmission                      Support spanning tree protocol STP/RSTP                      Support Vlan:VLAN/802.1Q Standard Vlan                      8.8G Switching Capacity                      5.36 Mpps Packet Forwarding Rate                      Network Management by WEB(http and https protocol)</p>		17,880,000
----	---------------------	---	---	------------



70	DH-PFS4226-24ET-240	<p>24-Port PoE Switch            Layer 2 management PoE switch            2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            24*10/100 Base-T (PoE power supply)            Port1/2 support Hi-PoE (60W), PoE+, PoE            Each power ≤30W, Total≤240W            Support IEEE802.3af, IEEE802.3at, Hi-PoE            250 meters long distance PoE transmission            Support spanning tree protocol STP/RSTP            Support Vlan:VLAN/802.1Q Standard Vlan            8.8G Switching Capacity            6.55 Mpps Packet Forwarding Rate            Network Management by WEB(http and https protocol)</p>		19,310,000
71	DH-PFS4226-24ET-360	<p>24-Port PoE Switch            Layer 2 management PoE switch            2*10/100/1000 Base-T (Combo port)            2*1000 Base-X (Combo port)            24*10/100 Base-T (PoE power supply)            Port1/2 support Hi-PoE (60W), PoE+, PoE            Each power ≤30W, Total≤360W            Support PoE, PoE+, Hi-PoE            'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300)            250 meters long distance PoE transmission            Support spanning tree protocol STP/RSTP            Support Vlan:VLAN/802.1Q Standard Vlan            8.8G Switching Capacity            6.55 Mpps Packet Forwarding Rate            Support Web management            management, PoE Setting/Event Statistics/Green PoE            Non-blocking video transmission</p>		23,020,000
72	PFT1300	<p>PoE Extender            1*10/100 Base-T PoE power receiving port            1*10/100 Base-T PoE power supply port, supply power for the next extender            1*10/100 Base-T PoE power supply port, supply power for IPC            Support passive PoE cascade power supply and Ethernet data exchange            Support IEEE 802.3af/at standard power supply IP Camera            able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption ≤8W),            maxtransmission distance 300m</p>		1,240,000
73	PFM700	<p>*1 Channel HDMI Transmission Signal            *1080P/1080I/720P/576P/576I/480P/480I Resolution Output Signal            *60M (max)Transmission Distance            *Input voltage DC5V            *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video signal:support HDMI 1.3</p>		3,580,000
74	DHI-NKB1000	<p>Keyboard to Control :            -Dahua High Speed Dome (all models)            -Dahua Standalone DVR            -Dahua Network High Speed Dome            -Network Video Server            Connection : RS485, RS422, USB, RS232 &amp; Network            Three Dimensional Joystick Control of PTZ Functions            Preset Position, Auto Scan, Auto Pan, Auto Tour &amp; Pattern Control            On-Screen Menu &amp; User Operation Procedure Tips            Connect to SmartPSS via USB</p>		15,600,000