

































2 MEGA PIXEL IP CAMERA SERIES				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
<u>VNC-2221</u>		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm & 4mm Lens, H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): plastic	4,850,000
<u>VNC-2220</u>		2MP	1/3" Progressive CMOS, ICR, 0 lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens, H.264/MJPEG, dual-stream, Intrusion Detection, Line Crossing Detection, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Bracket included	5,800,000
<u>VNC-2261</u>		2MP	1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, IK10, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Base bracket: metal Cover: plastic	5,000,000
<u>VNC-2260S</u>		2MP	1/3" Progressive CMOS, ICR, 0 lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, Intrusion Detection, Line Crossing Detection, IR range: up to 30m, Audio/Alarm IO	6,200,000
<u>VNC-5225</u>		2MP	1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology, Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 2.8/4/6mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, , Smart Series	تماس بگیرید
<u>VNC-5265</u>		2MP	1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology, Color: 0.005 lux @(F1.2, AGC ON), 0 lux with IR; 25fps/30fps(1920x1080); 2.8/4/6mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, , Smart Series	تماس بگیرید
<u>VNC-5230</u>		2MP	Darkfighter Ultra-low light technology, 1/1.8" Progressive Scan CMOS, ICR, 0 lux with IR, Slow shutter, 1920x1080: 50/60fps, 2.8-12mm/F1.4 Motorized VF lens with Smart Focus, H.264/MPEG4, Triple-Stream, Support SD/SDXC Card up to 128GB, IP67, DC12V/PoE, up to 50m IR range, Bracket & junction box included, - S: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Poepple count, , Smart Series	تماس بگیرید







3 MEGA PIXEL IP CAMERA				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
<u>VNC-2321</u>		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): Metal Back cover & Bracket(white part): plastic	6,200,000
<u>VNC-2361</u>		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Eyeball: Metal Cover: Plastic	6,200,000
<u>VNC-2331</u>		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8~12mm Vari-Focal lens, H.264+&H.264, IP67, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal -z: motorized vari-focal lens	تماس بگیریید
<u>VNC-4330S</u>		3MP	1/3" Progressive CMOS, ICR, 0.1lux/F1.2, 2048x1536:20fps, 2.8~12mm Vari-Focal lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, On-board card slot (up to 64GB), Mobile Monitoring Audio/Alarm IO	تماس بگیریید
<u>VNC-2371</u>		3MP	1/3" Progressive CMOS, ICR, 2304x1296:20fps, 2.8~12mm Vari-Focal lens, H.264+&H.264, IP67, IK10, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring -z: motorized vari-focal lens, Full metal	تماس بگیریید







4 MEGA PIXEL IP CAMERA				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
<u>VNC-2421</u>		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Front cover(black part): metal Back cover & Bracket(white part): plastic	7,000,000
<u>VNC-2461</u>		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8mm/F2.0 lens (4/6mm optional), H.264+&H.264, IP67, DWDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, Support mobile monitoring, Eyeball: Metal, Cover: Plastic	7,000,000
<u>VNC-4430</u>		4MP	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 2.8~12mm Vari-Focal lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 64GB (SD card not included), H.264+ Optimized Codec	تماس بگیریید
<u>VNC-2471</u>		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, IK10, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal -z: motorized vari-focal lens	تماس بگیریید
<u>VNC-4470</u>		4MP	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 2.8~12mm Vari-Focal lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support 128GB SD card, Vandal-proof housing, H.264+	تماس بگیریید
<u>VNC-2431</u>		4MP	1/3" Progressive CMOS, ICR, 2688x1520:20fps, 2.8~12mm VF lens, H.264+&H.264, IP67, 120db WDR, 3D DNR, BLC, IR range: up to 30m, DC12V & PoE, TF card slot, Support mobile monitoring, Full metal -s: motorized vari-focal lens	تماس بگیریید

5 MEGA PIXEL IP CAMERA				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
<u>VNC-5525</u>		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8/4/6/12mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, up to 80m IR distance, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Smart Series	تماس بگیریید
<u>VNC-5535S</u>		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8-12mm motorized VF lens; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 50m IR distance; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, S model: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Smart Series	تماس بگیریید
<u>VNC-5575</u>		5MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(2560x1920), 25fps/30fps(2560x1440, 2048x1536, 1920x1080); 2.8-12mm motorized VF lens; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0, up to 30m; All-metal housing, IP67, IK8; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, S model: Audio/Alarm IO, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection, Smart Series	تماس بگیریید
<u>VNC-5826</u>		8MP	1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux@(F1.2, AGC ON), 0 lux with IR; 20fps(3840x2160), 25fps/30fps (2560x1920, 2560x1440, 2048x1536, 1920x1080); 2.8/4/6/12mm lens optional; 120dB WDR; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR 2.0; All-metal housing, IP67; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot, up to 80m IR distance, Line crossing detection, Intrusion detection, Unattended baggage detection, Object removal detection, Face detection	تماس بگیریید

SPEED DOME IP CAMERA				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
<u>VNC-2280N</u>		2MP	2MP, 1/3" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.05lux/F2.0, B/W:0.01lux/F2.0, Zoom: 4x, Angle of View: 80-64.5 degree (Wide~Tele), Digital Zoom:16X, 1920x1080:30fps, Pan range:0°~350°; Tilt range: 0°~90°(Auto Flip), Pan Speed: 0.1° -100°/s, Tilt Speed: 0.1° -80°/s, 30m IR, POE&12VDC, /W: built-in WIFI	تماس بگیریید
<u>VNC-2281N</u>		2MP	2MP, 1/3" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance	تماس بگیریید
<u>VNC-4285N</u>		2MP	2MP, 1/2.8" CMOS, H.265+/H.265/H.264+/H.264/MJPEG, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3-129.0mm, Digital Zoom:12X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 120m IR Distance	تماس بگیریید
<u>VNC-5880</u>		8MP	8MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:36x, Focus:4.3-129.0mm, Digital Zoom:12X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 200m IR Distance	تماس بگیریید
<u>VNC-6280</u>		16MP	16MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:36x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° -400°/s, Tilt Speed: 0.1° -200°/s, 150m IR Distance	تماس بگیریید

1 MEGA PIXEL PINHOLE IP CAMERA				
MODEL	PICTURE	MP	DESCRIPTION	PRICE
<u>VNC-4190</u>		1MP	1/4" Progressive CMOS, H.264, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC,	8,000,000
4 MEGA PIXEL CUBE IP CAMERA				
<u>VNC-1490</u>		4MP	1/3" Progressive CMOS, H.264+, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB (SD card not included), built-in WIFI, H.264+ Optimized Codec	9,000,000
6 MEGA PIXEL FISH EYE IP CAMERA				
<u>VNC-6640S</u>		6MP	1/2" Progressive CMOS, H.264, Fish eye, ICR, 0lux with IR, Up to 3072 x 2048 resolution, 1.05mm/F2.8 lens, 360° Panoramic view, H.264/MJPEG, dual-stream, DC12V & PoE, Support on-board storage, Up to 15m IR, Audio/Alarm IO	تماس بگیریید
2 MEGA PIXEL ANPR IP CAMERA				
<u>VNC-6225S</u>		2MP	License Plate Recognition, Darkfighter ultra-low light technology, 1/1.8" progressive scan CMOS sensor, Full HD1080p, up to 60fps, 120dB WDR, Full smart feature-set, Motorized lens with Smart Focus, Up to 128GB on-board storage, Up to 50m IR range, IP67	تماس بگیریید
<u>VNC-6226S</u>		2MP	License Plate Recognition, Darkfighter ultra-low light technology, 1/1.8" progressive scan CMOS sensor, Full HD1080p, up to 60fps, 120dB WDR, Full smart feature-set, Visible Light, Motorized lens with Smart Focus, Up to 128GB on-board storage, Up to 50m IR range, IP67	تماس بگیریید

CONTROLLER				
MODEL	PICTURE	FEATURES	DESCRIPTION	PRICE
<u>VHN-K130</u>		Multi	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup, 256 units of DVR and SeedDome	تماس بگیریید
<u>VCU-1200</u>		Multi	<ul style="list-style-type: none"> Control up to 255 PTZ cameras Superior system compatibility : Multi protocols support OSD menu • 3D joystick control Control up to 255 PTZ cameras 	15,000,000
POE SWITCH				
MODEL	PICTURE	FEATURES	DESCRIPTION	PRICE
<u>VPS-8100</u>		1.8 Gbps switching fabric	IEEE 802.3at and IEEE 802.3af Power over Ethernet (PoE) compliant , Supports PoE power up to 123W for all PoE ports (8 port) and 230W for (16 port) ,4 kV surge protection for PoE ports , IEEE 802.3x flow control support , Plug-and-play installation , 1.8 Gbps switching fabric (8 port) and 7.2 Gbps switching fabric , 1.25 & 2.75 Mbits RAM Data Buffer , Sturdy metal enclosure, 30 watts per PoE	11,500,000
<u>VPS-16100</u>		7.2 Gbps switching fabric		27,000,000
<u>VPS-24100</u>		8.8 Gbps switching fabric		تماس بگیریید
<u>VCN-6</u>		U/UTP CAT6-4P-PVC-CM	305 meter network cable utp Cat6, E484059-Z (UL) CM 4PR 23AWG 75 U/UTP CAT6 VERIFIED TO ANSI/TIA-568-C.2 PVC, SOLID-Bare Copper	تماس بگیریید

4 CHANNEL NETWORK VIDEO RECORDER							
MODEL	PICTURE	Input	Output	Network interface	RECORD	DESCRIPTION	PRICE
<u>VNR-405</u>		40 Mbps	80Mbps	1 RJ 45 1000M		40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	5,800,000
<u>VNR-405P</u>		40 Mbps	80Mbps	1 RJ 45 1000M		40Mbps Bit Rate Input Max (up to 4-ch IP video), 2 SATA interfaces, 4 independent network POE interfaces for built-in switch, 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	9,800,000
8 CHANNEL NETWORK VIDEO RECORDER							
<u>VNR-805</u>		80 Mbps	80Mbps	1 RJ 45 1000M		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	9,000,000
<u>VNR-805E</u>		80 Mbps	80Mbps	1 RJ 45 1000M		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent network interfaces for built-in switch, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	12,000,000
<u>VNR-805P</u>		80 Mbps	80Mbps	1 RJ 45 1000M		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent network POE interfaces for built-in switch, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	14,000,000
<u>VNR-808</u>		80 Mbps	80Mbps	1 RJ 45 1000M		80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 8 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, including network delay, packet loss, etc	10,500,000

vertina

EMPOWERED BY INNOVATION

TURBO HD SOLUTION PRICE LIST 2018

لیست قیمت تجهیزات حفاظتی NETWORK ورتینا ویژه ۲۰۱۸ میلادی



16 CHANNEL NETWORK VIDEO RECORDER						
MODEL	PICTURE	Input	Output	RECORD	DESCRIPTION	PRICE
<u>VNR-1605</u>		160 Mbps	80Mbps	16-ch 5mp camera	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 5 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	9,500,000
<u>VNR-1605E</u>		160 Mbps	80Mbps	16-ch 5mp camera	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent network interfaces for built-in switch, 380 1U case , Third-party network cameras supported , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	16,000,000
<u>VNR-1605P</u>		160 Mbps	80Mbps	16-ch 5mp camera	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent network POE interfaces for built-in switch, 380 1U case , Third-party network cameras supported , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	19,000,000
<u>VNR-1608</u>		160 Mbps	80Mbps	16-ch 8mp camera	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case , Third-party network cameras supported , Up to 8 Megapixels resolution recording , HDMI and VGA output at up to 1920x1080P resolution , Support network detection, 1 RJ 45 1000M, including network delay, packet loss, etc	13,000,000
<u>VNR-1612 P4</u>		160 Mbps	256Mbps	16ch 12mp camera	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19" 4K resolution(up to 12MP), H.265/H.264+/H.264 supported	تماس بگیرید





vertina



EMPOWERED BY INNOVATION





TURBO HD SOLUTION PRICE LIST 2018




لیست قیمت تجهیزات حفاظتی NETWORK ورتینا ویژه ۲۰۱۸ میلادی

32 / 64 CHANNEL NETWORK VIDEO RECORDER						
MODEL	PICTURE	Input	Output	RECORD	DESCRIPTION	PRICE
<u>VNR-3212 P4</u>		256 Mbps	256Mbps	32ch 12mp camera	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 2U case,19" 4K resolution(up to 12MP), H.265/H.264+/H.264 supported	تماس بگیریید
<u>VNR-3212P16</u>		320 Mbps	256Mbps	32ch 12mp camera	Third-party network cameras supported , Up to 12 Megapixels resolution recording , Support 2-ch HDMI, 2-ch VGA, HMDI1 at up to 4K(3840x2160) , 2 RJ 45 1000M, Up to 32 IP cameras can be connected with 320M incoming bandwidth , Up to 16 SATA interfaces Support HDD hot swap with RAID0,1,5,6,10 storage , scheme configurable , Support various VCA detection alarm and VCA earch ,Support H.265/H.264/MPEG4 video formats, RAID0, RAID1, RAID5, RAID6, RAID10	تماس بگیریید
<u>VNR-6412P16</u>		320 Mbps	256Mbps	64ch 12mp camera	Third-party network cameras supported , Up to 12 Megapixels resolution recording , Support 2-ch HDMI, 2-ch VGA, HMDI1 at up to 4K(3840x2160) , 2 RJ 45 1000M, Up to 64 IP cameras can be connected with 320M incoming bandwidth , Up to 16 SATA interfaces Support HDD hot swap with RAID0,1,5,6,10 storage , scheme configurable , Support various VCA detection alarm and VCA earch ,Support H.265/H.264/MPEG4 video formats, RAID0, RAID1, RAID5, RAID6, RAID10	تماس بگیریید
<u>Vertia 3500+ ServerStation</u>		32 * 4 Mbps	16 * 4 Mbps	Server Station	• 32 Channel connected cameras • Central management system • Supports GPU hardware decoding to save CPU resources • Windows Embedded System 7 • Storage 4 HDDs connectable • Third-party product integration via ONVIF • Decoding performance 2*4K / 9 * 1080p	تماس بگیریید

VNR-1605 P		100 Mbps	240Mbps	1 RJ 45 1000M	8-ch 1080P	100Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	CALL
VNR-3205 P		200 Mbps	160Mbps	1 RJ 45 1000M	8-ch 1080P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	CALL
VNR-3212-P16		320 Mbps	256Mbps	16	16-ch 1080P	320Mbps Bit Rate Input Max(up to 32-ch IP video), 16 SATA Interfaces, alarm I/O: 16/4, RAID0,1,5,10 supported, 3U case,19" 4K resolution(up to 12MP),H.265/H.264+/H.264 support	CALL
VNR-6412-P16		320 Mbps	256Mbps	16	16-ch 1080P	320Mbps Bit Rate Input Max(up to 64-ch IP video), 16 SATA Interfaces, alarm I/O: 16/4, RAID0,1,5,10 supported, 3U case,19"4K resolution(up to 12MP), H.265/H.264+/H.264 support	CALL

<u>VNR-405E</u>		40 Mbps update to 40Mbps	80Mbps	1 RJ 45 1000M	4-ch 1080P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	5,800,000
<u>VNC-5310</u>		3MP	Box	-	120dB WDR	1/3" Progressive Scan CMOS, ICR, Color:0.1Lux/F1.2, B/W:0.01Lux/F1.2, Slow shutter, 2048 x 1536: 20fps, H.264/MJPEG/MPEG4, Triple-Stream, Support SD/SDXC Card up to 64GB, Audio & Alarm I/O, AC24V/DC12V/PoE	موجود هست تماس بگیریید
<u>VNC-4530</u>		5MP	VF IR Bullet	2.8~12mm VF lens	DWDR	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1920:20fps, 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB (SD card not included), H.264+ Optimized Codec	موجود هست تماس بگیریید
<u>VNC-4370S</u>		3MP	1/3" Progressive CMOS, ICR, 0lux with IR, 2048x1536:20fps 2.8~12mm VF lens, IP66, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, On-board card slot (up to 64GB), Vandal-proof, Audio/Alarm IO				تماس بگیریید
<u>VNC-2230</u>		2MP	1/3" Progressive CMOS, ICR, 0 lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm Vari-Focal lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, True WDR 120db, 3D DNR, BLC, Intrusion Detection, Line Crossing Detection, IR: up to 30m, On-board card slot (up to 64GB)				8,900,000

<u>VNC-4460S</u>		4MP	"1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support onboard storage up to 128GB(SD card not included), H.264+-S: Audio/alarm IO	9,900,000
-------------------------	---	-----	--	-----------

www.hikpersian.ir
شرکت فناوریان تصویرنوین
021-66754022



فناوران تصویر نوین