
















# فناوران تصویر نوین
















## Network Camera - NVR








Items	Description	User Price	
<b>20 Series</b>			
1	DS-2CD2020F-I 1/3" Progressive CMOS, ICR, Olux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board	IRR 12,630,000	
2	DS-2CD2042WD-I 1/3" Progressive CMOS, ICR, Olux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67	IRR 17,800,000	
3	DS-2CD2052-I 1/3" Progressive CMOS, ICR, Olux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams IP67, DC12V & PoE	IRR 22,700,000	
<b>21 Series</b>			
4	DS-2CD2120F-I 1/3" Progressive CMOS, ICR, Olux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream	IRR 12,630,000	
6	DS-2CD2142FWD-IS 1/3" Progressive CMOS, ICR, Olux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, IK10, DC12V & PoE, DWDR	IRR 19,290,000	
7	DS-2CD2152F-IS 1/3" Progressive CMOS, ICR, Olux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on board	IRR 23,890,000	








23 Series			
9	DS-2CD2342WD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67	IRR 20,820,000 
24 Series			
11	DS-2CD2420F-IW	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, 120dB WDR, DC12V & PoE	IRR 12,630,000 
12	DS-2CD2442FWD-IW	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, DC12V & PoE, 120dB WDR, 3D	IRR 17,410,000 
25 Series			
	DS-2CD2520F	Up to 2 megapixel (1920 x 1080 @ 30 fps) resolution, Standard video compression with high compression	
	DS-2CD2522FWD-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920*1080:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA	
13	DS-2CD2542FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m,	IRR 22,700,000 
27 Series			
20	DS-2CD2720F-I	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile	IRR 22,530,000 
20	DS-2CD2720FWD-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps(P)/30fps(N), 2.8~12mm VF lens, 120dB H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile	IRR 34,860,000 

G0 Series				
14	DS-2CD1043G0-I	1/3" Progressive CMOS, ICR, 0lux With IR, 2560x1440:20fps(P)/30fps(N), Fixed lens, H.265+/H265/H264+/H264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included)	IRR 13,310,000	
15	DS-2CD1643G0-I(Z)	1/3" Progressive CMOS, ICR, 0lux with IR, 2560 x 1440@20fps(P)/30fps(N), 2.8~12mm VF lens, H.265+, H.265, H.264+, H.264MJPEG, dual-stream, IP67, DC12V & PoE, 120 dB WDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included)	IRR 23,890,000	
16	DS-2CD2043G0-I	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2560x1440:30fps(P)/30fps(N), Fixed lens, IP67, H.265+, H.265, H.264+, H.264MJPEG, ; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included)	IRR 16,210,000	
17	DS-2CD2063G0-I	1/3" Progressive CMOS, ICR, 0.01lux/F1.2 fixed lens, IP67, 3072 x 2048@20 fps/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included)	IRR 19,460,000	
18	DS-2CD2083G0-I	1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 3840 x 2160 @15 fps, IP67, H.265+, H.265, H.264+, H.264/MJPEG, ; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included)	IRR 22,870,000	
G0 Series				
20	DS-2CD1143G0-I	1/3" Progressive CMOS, ICR, 0.01 lux @F1.2, 2560 x 1440@20fps(P)/30fps(N), , H.265+, H.265, H.264+, H.264/MJPEG, dual-stream, IP67, IK10,DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, fixed lens	IRR 14,000,000	
21	DS-2CD1743G0-I(Z)	1/3" Progressive CMOS, ICR, 0lux with IR,2560 x 1440@ 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, 120dB, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included) IP67	IRR 23,890,000	











22	DS-2CD2143G0-IS	1/3" Progressive Scan CMOS, 2688 x 1520 @30fps,120dB WDR,3D DNR,Up to 30 meters IR,H.265+, H.265, H.264+, H.264,3 streams,Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB,IP67, IK10,2 Behavior analyses, and face detection	IRR 17,750,000	
23	DS-2CD2163G0-IS	1/3" Progressive CMOS, ICR, , 2688 x 1520 @30fps,Fixed lens, H.264+/H.264/MJPEG; 3 streams, IP67 ,IK10, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m, support on-board storage up to 128GB	IRR 21,160,000	
24	DS-2CD2183G0-IS	1/3" Progressive CMOS, ICR, 3840 x 2160 @15 fps, Fixed lens, IP67 IK10, H.265+, H.265, H.264+, H.264MJPEG, ; 3 streams, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 30m	IRR 24,920,000	
29 Series				
27	DS-2CD2955FWD-IS	1/3" Progressive CMOS, Electronic Day/night, Up to 2560 x 1920 @30fps resolution, 1.6mm/F1.6 fixed lens, 180° Panoramic view,H.265, H.265+, H.264+, H.264, 3D DNR,120 dB, DC12V & PoE, Support on-board storage up to 128GB	IRR 56,800,000	
2T Series				
29	DS-2CD2T42WD-I8	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG,VCA functions: 3 streams, IP67, DC12V & PoE	IRR 22,700,000	
30	DS-2CD2T52-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE	IRR 24,920,000	
G0 Series				

30	DS-2CD2T43G0-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 2560 x 1440@30fps, /Fixed lens , H.265+, H.265, H.264+, H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, , EXIR LEDs, up to 50m IR range,2 Behavior analyses, and face detection	IRR 18,940,000	
30	DS-2CD2T63G0-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 3072 x 2048@20 fps,/Fixed lens , H.265+, H.265, H.264+, H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB	IRR 22,190,000	
30	DS-2CD2T63G0-I8	1/3" Progressive CMOS, ICR, 0lux with IR, 3072 x 2048@20 fps,/Fixed lens , H.265+, H.265, H.264+, H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB	IRR 23,550,000	
30	DS-2CD2T83G0-I5	1/3" Progressive CMOS, ICR, 0lux with IR, 3840 x 2160 @15 fps, fixed lens , H.265+, H.265, H.264+, H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB	IRR 26,620,000	
30	DS-2CD2T83G0-I8	1/3" Progressive CMOS, ICR, 0lux with IR, 3840 x 2160 @15 fps, fixed lens , H.265+, H.265, H.264+, H.264/MJPEG, 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, EXIR LEDs, up to 80m IR range	IRR 27,990,000	
<b>2F Series</b>				
31	DS-2CD2F52F-IS	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps,2048x1536: 25fps(P)/30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3		
<b>2D Series</b>				
32	DS-2CD2D14WD	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens.		
<b>2E Series</b>				

33	DS-2CD2E20F-W	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), H.264/MJPEG, dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up		
<b>2Q Series</b>				
34	DS-2CD2Q10FD-IW	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream,		
35	S-2CV2Q21FD-IW/32GB-	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board		
<b>2U Series</b>				
36	S-2CV2U21FD-IW/32GB-	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up		
<b>IP PTZ Camera</b>				
<b>4" IR PTZ</b>				
37	DS-2DE4220IW-DE	2MP, 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:268° and Tilt: 11°	IRR 67,510,000	
<b>5" IR PTZ</b>				
38	DS-2DE5220IW-AE	H.265+/H.265/H.264+/H.264; 2MP, 1/3" CMOS, 3D DNR, ICR, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, 1920x1080:30fps. Pan	IRR 112,260,000	
<b>5" PTZ</b>				
39	DS-2DE5230W-AE	H.265+/H.265/H.264+/H.264 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X,	IRR 116,970,000	
<b>7" IR PTZ</b>				





41	DS-2DE7220IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus:4.3- 129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 117,750,000	
41	DS-2DE7230IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3- 129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 136,200,000	
41	DS-2DE7320IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 3MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus:4.3- 129.0mm, Digital Zoom:16X,2048 x 1536@30fps Resolution Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 134,240,000	
41	DS-2DE7330IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 3MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3- 129.0mm, Digital Zoom:16X,2048 x 1536@30fps Resolution Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 159,750,000	
41	DS-2DE7420IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 4MP, 1/2.9" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:20x, Focus:4.3- 129.0mm, Digital Zoom:16X,2560 x 1440 @30fps Resolution Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 163,280,000	
41	DS-2DE7430IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 3MP, 1/2.9" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3- 129.0mm, Digital Zoom:16X, 2560 x 1440 @30fps Resolution Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 186,830,000	
41	DS-2DE7530IW-AE	11.2057/11.2057/11.2044/11.2044 codec, 5MP, 1/1.9" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:30x, Focus:4.3- 129.0mm, Digital Zoom:16X, 2592 x 1944@30fps Resolution Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -170°/s, 150°/s	IRR 203,320,000	

**PanoVu Mini Series 2MP 4x Network PTZ Camera**

41	DS-2PT3326IZ-DE3	H.265/H.264/H.264 CODEC, 2MP, 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom:4x, Focus:4.3-129.0mm, Digital Zoom:8X, 1920x1080:30fps, Pan Speed: 0.1° -160°/s, Tilt Speed: 0.1° -120°/s, 150m IR Distance, Hi-Res 24VAC	IRR 70,000,000	
<b>NETWORK CAMERA -NVR</b>				
69	DS-7108NI-E1/M	4-ch, 1-ch, RCA (2.0 Vp-p, 1kΩ) ,40 Mbps,4 MP/3 MP/1080p/1.3 MP/UXGA/720p/VGA/4CIF /DCIF/2CIF/CIF/QCIF ,Main stream: 50 fps (P)/60 fps (N)		
47	DS-7604NI-E1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 12,390,000	
48	DS-7604NI-E1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case		
49	DS-7604NI-K1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 14,860,000	
50	DS-7604NI-K1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 20,170,000	
49	DS-7604NI-Q1	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	IRR 14,860,000	
50	DS-7604NI-Q1/4P	40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case	IRR 20,170,000	
53	DS-7608NI-E2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 17,340,000	
54	DS-7608NI-E2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O:	IRR 29,010,000	



53	DS-7608NI-K2	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 21,230,000	
54	DS-7608NI-K2/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O:	IRR 33,610,000	
53	DS-7608NI-Q1	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 20,000,000	
54	DS-7608NI-Q1/8P	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O:	IRR 32,000,000	
53	DS-7616NI-Q1	160Mbps Bit Rate Input Max (up to 16-ch IP video), 1 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	IRR 21,000,000	
59	DS-7616NI-Q2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case,	IRR 44,220,000	
59	DS-7616NI-K2/16P	160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case,	IRR 44,220,000	
60	DS-7716NI-E4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 37,500,000	
61	DS-7716NI-E4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4,	IRR 58,020,000	
62	DS-7716NI-K4	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 46,350,000	
63	DS-7716NI-K4/16P	160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4,	IRR 65,800,000	
64	DS-7732NI-K4	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 58,370,000	

65	DS-7732NI-K4/16P	256Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4,	IRR 77,120,000	
66	DS-7732NI-E4	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	IRR 49,180,000	
67	DS-7732NI-E4/16P	200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4,	IRR 69,340,000	
<b>All In One Series</b>				
70	DS-7600NI-E1/A/1T	80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, 22 inch monitor, <b>1TB HDD WD10JUCT pre-installed</b>		

شماره تماس شرکت: ۶۶۷۵۴۰۲۲

















