











# لیست قیمت محصولات هایک ویژن




IP CAMERA CONSUMER SERIES

تصویر	مدل	توضیحات	قیمت (ریال)
 <p>DS-2CD2D14WD HIKVISION</p>	<b><u>DS-2CD2D14WD</u></b>	1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, <b>100dB WDR</b> , 3D DNR, BLC, Support Mobile Monitoring via EZVIZ P2P	۲۰۷۰۰۰۰۰
 <p>DS-2CD2E20F-W HIKVISION</p>	<b><u>DS-2CD2E20F-W</u></b>	1/3" Progressive CMOS, Day/night, 0.1lux/F1.2, 1920x1080:25fps(P)/30fps(N), 4mm lens (2.8/6mm optional), <b>H.264/MJPEG</b> , dual-stream, DC12V & PoE, DWDR, 3D DNR, BLC, Support on-board storage up to <b>64GB</b> (SD card not included), Support Mobile Monitoring via EZVIZ P2P, Color Lens Cover optional (Black, Silver, Golden) <b>-W: Built-in Wi-Fi</b>	۲۹۴۹۶۰۰۰
 <p>DS-2CD2Q10FD-IW HIKVISION</p>	<b><u>DS-2CD2Q10FD-IW</u></b>	1/4" Progressive CMOS, ICR, 0lux with IR, 4mm/F2.0 (2.8/6mm optional), Pan/tilt rotation, 1280x720:25fps(P)/30fps(N), H.264/MJPEG, dual-stream, DC5V, DWDR, 3D DNR, BLC, Support on-board card slot (SD card not included), Audio, Alarm IO, Up to 10m IR, PIR, <b>Wi-Fi with WPS</b> connection, Support Mobile Monitoring via EZVIZ P2P	۲۹۸۴۰۰۰۰
 <p>DS-2CV2Q21FD-IW HIKVISION</p>	<b><u>DS-2CV2Q21FD-IW</u></b>	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, H.264/MJPEG, dual-stream, 3D DNR, 5m IR, PT function (Pan: 0° ~ 355°; Tilt: -10° ~ 90°), support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply. Default: No SD card included. <b>/32GB-T: Include 16GB sd card.</b>	۲۳۰۰۴۰۰۰
 <p>DS-2CV2U21FD-IW HIKVISION</p>	<b><u>DS-2CV2U21FD-IW</u></b>	1/2.8" Progressive CMOS, ICR, 0lux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens, <b>H.264/MJPEG</b> , dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in <b>Wi-Fi</b> , 12VDC power supply. <b>/32GB-T: Include 32GB sd card.</b>	۲۰۷۶۰۰۰۰




**IP CAMERA 2MP**



تصویر	مدل	توضیحات	قیمت (ریال)
	<b><u>DS-2CD1023G0-I</u></b>	λ 1/2.8" progressive scan CMOS λ Up to 2.0 megapixel λ 2.8 mm/4 mm/6 mm fixed focal lens λ Up to 30 m IR range λ Dual stream λ Digital WDR (Wide Dynamic Range) λ 3D DNR (Digital Noise Reduction) λ PoE (Power over Ethernet) λ IP67 λ Mobile monitoring via Hik-Connect or iVMS-4500	۲۴۱۷۰۰۰۰
	<b><u>DS-2CD1123G0-I</u></b>	1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67, IK10 Dual stream Digital WDR (Wide Dynamic Range)	۲۵۸۷۰۰۰۰
	<b><u>DS-2CD1623G0-I</u></b>	1/2.8" progressive scan CMOS BLC/3D DNR/ROI 1920 × 1080@30fps Up to 30 m IR range 2.8 mm to 12 mm varifocal lens IP67 H.265+, H.265, H.264+, H.264 Digital WDR Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۴۹۱۹۰۰۰۰
	<b><u>DS-2CD1623G0-IZ</u></b>	1/2.8" progressive scan CMOS BLC/3D DNR/ROI 1920 × 1080@30fps Up to 30 m IR range 2.8 mm to 12 mm varifocal lens IP67 H.265+, H.265, H.264+, H.264 Digital WDR Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۵۵۱۲۰۰۰۰
	<b><u>DS-2CD1723G0-I</u></b>	1/2.8" progressive scan CMOS 3D DNR (Digital Noise Reduction) 1920 × 1080@30fps Up to 30 m IR range 2.8 mm to 12 mm manual/motorized (with -Z) varifocal lens PoE (Power over Ethernet) IP67, IK10 H.265+, H.265, H.264+, H.264 Dual stream Digital WDR (Wide Dynamic Range)	۴۹۱۹۰۰۰۰






تصویر	مدل	توضیحات	قیمت (ریال)
	<b><u>DS-2CD2620F-I</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -Z: Motorized VF lens	۵۰۹۹۰۰۰۰
	<b><u>DS-2CD2543G0-IS</u></b>	4MP IR NETWORK Mini DOME CAMERA 1/3" 4MP progressive scan CMOS 2688 × 1520@30fps 4 mm lens , 0 lux IR on Max IR distance: 10 meters H.265+,H.264,MJPEG video compression 3DDNR,BLC, WDR(120dB),ROI,VCA, Micro SD, (Up to 128GB), Reset Button Built In MIC , Two Way Talk , 1 Alarm I/O PoE, DC12V, IP67,IK08 ,3 axis adjustment- • EXIR Onvif support	۵۷۶۵۰۰۰۰
	<b><u>DS-2CD2720F-I</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Vandal-proof, Support Mobile Monitoring via EZVIZ P2P	۴۲۸۰۰۰۰۰
	<b><u>DS-2CD2520F</u></b>	2MP NETWORK Mini DOME CAMERA 1/2.8" 2MP progressive scan CMOS Up to 1920*1080 resolution (25fps) 4 mm lens H.264,MJPEG video compression 3DDNR,BLC, DWDR,ROI, Micro SD (Up to 64GB),Reset Button PoE, DC12V, IP66,3 axis adjustment Onvif support	۲۰۵۶۸۰۰۰
	<b><u>DS-2CD2720F-IZ</u></b>	Up to 2.0 megapixel (1920 × 1080) high resolution λ Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB λ Great performance and long lifespan Infrared LED, Approx. 20 to 30 meters IR range λ IR cut filter with auto switch λ DC12V & PoE λ Motorized lens λ Digital Wide Dynamic Range λ 3D Digital Noise Reduction λ Backlight Compensation λ Auto Electronic Shutter λ 3-axis adjustment λ IP66 weather-proof protection λ IK10 vandal-proof	۴۴۹۱۶۰۰۰

protection λ Mobile Monitoring via Hik-Connect or iVMS-4500


تصویر	مدل	توضیحات	قیمت (ریال)
<p>۱۶</p> 	<b><u>DS-2CD2020F-I</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (6mm optional), H.264/MJPEG, dual-stream, IP66, DWDR, 3D DNR, BLC, Support on-board storage (SD card not included), IR range: up to 30m, Bracket included, Housing: plastic and metallic, DC12V & external PoE cable, , Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi	۲۰۰۲۸۰۰۰
<p>۱۷</p> 	<b><u>DS-2CD2120F-I</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P	۲۰۰۲۸۰۰۰
<p>۱۸</p> 	<b><u>DS-2CD2120F-IS</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Support on-board storage (SD card not included), Support Mobile Monitoring via EZVIZ P2P -S: Audio/Alarm IO connectors	۲۰۰۲۸۰۰۰

۱۹		<p><b><u>DS-2CD2122FWD-IS</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, VCA functions, 3 streams, IP67, IK10, DC12V &amp; PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO</p>	call
۲۰		<p><b><u>DS-2CD2420F-IW</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 1920x1080:25fps(P)/30fps(N), 4mm/F2.0 lens (2.8mm, 6mm optional), H.264/MJPEG, dual-stream, DC12V &amp; PoE, DWDR, 3D DNR, BLC, IR: up to 10m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P -W: Built-in Wi-Fi with WPS</p>	۳۱۳۸۰۰۰۰

	تصویر	مدل	توضیحات	قیمت (ریال)
۲۱		<p><b><u>DS-2CD1123G0E-I</u></b></p>	<p>2MP IR Fixed Network Dome Camera 1/2.8progressive scan CMOS 1920 × 1080@30fps 2.8mm/4 mm fixed lens H.265+/H.265/H.264+/H.264 3D DNR Up to 30 m IR range IP67, IK10</p>	۲۵۰۲۰۰۰۰

۲۲	 <p>DS-2DE7232IW-AE <b>HIKVISION</b></p>	<p><b><u>DS-2DE7232IW-AE</u></b></p>	<p>1/2.8" progressive scan CMOS Up to 1920 × 1080@60fps resolution 32× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus Up to 150 m IR distance 24 VAC &amp; Hi-PoE Support H.265+/H.265 video compression</p>	۲۷۳۵۱۰۰۰۰
۲۳	 <p>DS-2PT3326IZ-DE3 <b>HIKVISION</b></p>	<p><b><u>DS-2PT3326IZ-DE3</u></b></p>	<p>Hikvision DS-2PT3326IZ-DE3 (2.8-12mm) PanoVu Mini Series Network PTZ Camera, with the integration design, is able to capture 360° images with the panoramic cameras as well as close-up images with the PTZ camera.</p>	۱۵۲۹۲۰۰۰۰

**IP CAMERA 3MP**

تصویر	مدل	توضیحات	قیمت (ریال)	
۲۴	 <p>DS-2CD2T35FWD-18 <b>HIKVISION</b></p>	<p><b><u>DS-2CD2T35FWD-18</u></b></p>	<p>Up to 3 megapixel high resolution Max. 2048 × 1536 @30fps 2.8 mm/4mm/6mm/8 mm/12mm fixed lens, optional Ultra-low light H.265, H.265+, H.264+, H.264 120dB Wide Dynamic Range 3D Digital Noise Reduction</p>	۶۸۸۰۰۰۰۰







## IP CAMERA 4MP



تصویر	مدل	توضیحات	قیمت (ریال)
 	<b><u>DS-2CD1043G0-I</u></b>	1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67 Dual stream Digital WDR (Wide Dynamic Range)	۳۳۰۸۰۰۰۰
 	<b><u>DS-2CD1143G0-I</u></b>	1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range 2.8 mm/4 mm/6 mm fixed lens PoE (Power over Ethernet) H.265+, H.265, H.264+, H.264 IP67, IK10 Dual stream Digital WDR (Wide Dynamic Range)	۳۴۷۷۰۰۰۰
 	<b><u>DS-2CD1643G0-I</u></b>	1/3" progressive scan CMOS BLC/3D DNR/ROI 2560 × 1440@20fps Up to 30 m IR range 2.8 mm to 12 mm varifocal lens IP67 H.265+, H.265, H.264+, H.264 120 dB WDR Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON) Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۵۹۳۶۰۰۰۰
 	<b><u>DS-2CD1743G0-I</u></b>	1/3" progressive scan CMOS 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range 2.8 mm to 12 mm manual/motorized (with -Z) varifocal lens PoE (Power over Ethernet) IP67 H.265+, H.265, H.264+, H.264 Dual stream 120 dB WDR (Wide Dynamic Range)	۵۳۴۳۰۰۰۰


تصویر	مدل	توضیحات	قیمت (ریال)
-------	-----	---------	-------------





۳۹	 <p>DS-2CD2042WD-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD2042WD-I</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (6mm optional), <b>H.264+/H.264/MJPEG</b>, VCA functions, <b>3 streams</b>, IP67, DC12V &amp; PoE, 120dB WDR, 3D DNR, <b>BLC</b>, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service</p>	۲۷۸۷۶۰۰۰
۳۰	 <p>DS-2CD2142FWD-IS <b>HIKVISION</b></p>	<p><b><u>DS-2CD2142FWD-IS</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520: 20fps, 4mm/F2.0 lens (2.8/6mm optional), <b>H.264+/H.264/MJPEG</b>, VCA functions, <b>3 streams</b>, IP67, IK10, DC12V &amp; PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO</p>	۲۷۹۱۰۰۰۰
۳۱	 <p>DS-2CD2342WD-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD2342WD-I</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), <b>H.264+/H.264/MJPEG</b>, VCA functions; <b>3 streams</b>, IP67, DC12V &amp; PoE, 120dB <b>WDR</b>, 3D DNR, BLC, EXIR range: up to 30m</p>	۴۶۵۶۰۰۰۰
۳۲	 <p>DS-2CD2442FWD-IW <b>HIKVISION</b></p>	<p><b><u>DS-2CD2442FWD-IW</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0.01lux/F1.2, 2688x1520:20fps, 4mm/F2.0 lens (2.8/6mm optional), <b>H.264+/H.264/MJPEG</b>, VCA functions; <b>3 streams</b>,DC12V &amp; PoE, <b>120dB WDR</b>, 3D DNR, BLC, IR range: up to 10m, support on-board storage up to 128GB(SD card not included), <b>built-in WIFI</b></p>	۱۸۷۶۸۰۰۰
۳۳	 <p>DS-2CD2542FWD-IS <b>HIKVISION</b></p>	<p><b><u>DS-2CD2542FWD-IS</u></b></p>	<p>1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), <b>H.264+/H.264/MJPEG</b>, VCA functions; <b>3 streams</b>, IP67, DC12V &amp; PoE, <b>120dB WDR</b>, 3D DNR, BLC, IR: up to 10m, support on-board storage up to <b>128GB</b>(SD card not included), HIK-Connect cloud service -S: Built-in MIC, audio/alarm IO</p>	۵۷۶۵۰۰۰۰

تصویر	مدل	توضیحات	قیمت (ریال)
 <p>DS-2CD2T42WD-I5 HIKVISION</p>	<b><u>DS-2CD2T42WD-I5</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG,VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I5: 2pcs EXIR LEDs, up to 50m IR range	call
 <p>DS-2CD2T42WD-I8 HIKVISION</p>	<b><u>DS-2CD2T42WD-I8</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F1.4 lens (6mm optional), H.264+/H.264/MJPEG,VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, HIK-Connect cloud service -I8: 4pcs EXIR LEDs, up to 80m IR range	call
 <p>DS-2CD2443G0-IW HIKVISION</p>	<b><u>DS-2CD2443G0-IW</u></b>	4MP IR Cube NETWORK CAMERA 1/2.7" 4MP progressive scan CMOS Up to 2688x1520 resolution (30 fps) 2.8mm lens , 0 lux IR on Max IR distance: 10 meters , PIR Range :10m-EXIR H.265+ /H.265/H.264+/H.264/ MJPEG video compression 3DDNR,BLC, WDR(120DB),ROI,VCA,Micro SD (Up to 128GB), Built-in WIFI, Built In MIC & Speaker , Two Way Talk , 1 Alarm I/O PoE, DC12V Onvif support	۴۱۹۸۰۰۰۰
 <p>DS-2CD2942F-I HIKVISION</p>	<b><u>DS-2CD2942F-I</u></b>	1/3" Progressive Scan CMOS Up to 4 megapixel resolution Fisheye & PTZ view 3D DNR I: IR range approx. 8 meters W: Support Wi-Fi, support WPS configuration with one touch S: audio & alarm I/O Support 128G on-board storage 12 VDC ± 10% / PoE	call

تصویر	مدل	توضیحات	قیمت (ریال)
 <p>DS-2CD2043G0-I <b>HIKVISION</b></p>	<b><u>DS-2CD2043G0-I</u></b>	1/3" Progressive Scan CMOS 2560 × 1440@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	۴۳۱۰۰۰۰۰
 <p>DS-2CD2143G0-IS <b>HIKVISION</b></p>	<b><u>DS-2CD2143G0-IS</u></b>	1/3" Progressive Scan CMOS 2560 × 1440@30fps 2.8mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	۴۴۱۰۰۰۰۰
 <p>DS-2CD2643G0-IZS <b>HIKVISION</b></p>	<b><u>DS-2CD2643G0-IZS</u></b>	1/3" Progressive Scan CMOS 2560 × 1440@30fps 2.8 to 12 mm Varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 behavior analyses, and face detection BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	۸۹۰۴۰۰۰۰
 <p>DS-2CD2743G0-IZS <b>HIKVISION</b></p>	<b><u>DS-2CD2743G0-IZS</u></b>	1/3" Progressive Scan CMOS 2560 × 1440@30fps 2.8 to 12 mm Varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 behavior analyses, and face detection BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	۸۹۰۴۰۰۰۰

۴۲	 <p>DS-2CD2632F-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD2632F-I</u></b></p> <p>1/3" Progressive Scan CMOS 2560 × 1440@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment</p>	۵۷۶۷۰۰۰۰
----	---	---	----------

تصویر	مدل	توضیحات	قیمت (ریال)
۴۳	 <p>DS-2CD1043G0E-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD1043G0E-I</u></b></p> <p>4MP EXIR Fixed Bullet Network Camera 1/3Progressive Scan CMOS 2560 × 1440@20fps 2.8/4 mm fixed lens (Color: 0.028 Lux @ (F2.0, AGC ON) H.265, H.265+, H.264, H.264+ BLC/HLC/3D DNR/ROI IR range: Up to 30 m 3Axis adjustment IP67</p>	۲۸۸۴۰۰۰۰
۴۴	 <p>DS-2CD2143G0-IS(BLACK) <b>HIKVISION</b></p>	<p><b><u>DS-2CD2143G0-IS(BLACK)</u></b></p> <p>1/3"Progressive Scan CMOS 2688 × 1520@30fps 2.8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment Audio &amp; Alarm I/O</p>	۴۴۷۲۰۰۰۰

خیابان جمهوری، تقاطع حافظ، مجتمع نادری، طبقه دوم، شماره ۲۲





۴۵



**DS-2CD2643G1-IZS**

Minimum Illumination: Color: 0.01 lux @ (f/1.2, AGC on), 0.018 lux @ (f/1.6, AGC on), 0 Lux with IR  
2688 x 1520 Resolution @ 30 fps  
2.8 to 12 mm Motorized Varifocal Lens  
H.265+, H.265, H.264+, H.264  
Main Stream: 30 fps (2688 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080)  
EXIR 2.0 Range Up to 165 ft (50 m)  
12 VDC and PoE+ (802.3at)

۸۲۴۹۰۰۰۰

**IP CAMERA 5MP**

تصویر	مدل	توضیحات	قیمت (ریال)
<p>۴۶</p> <p><b>HIKVISION</b></p>	<b><u>DS-2CD2052-I</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560x1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 30m, Full metallic housing, HIK-Connect cloud service	۴۱۴۲۰۰۰۰
<p>۴۷</p> <p><b>HIKVISION</b></p>	<b><u>DS-2CD2T63G0-I8</u></b>	6MP EXIR NETWORK BULLET CAMERA 1/2.9" 6MP progressive scan CMOS Up to 3072x 2048 resolution (20 fps) 2.8mm lens , 0 lux IR on Max IR distance: 80 meters H.265+,H.265,H.264+,H.264,MJPEG video compression 3DDNR,BLC,WDR(120dB),ROI,VCA,Face Detection, Micro SD (Up to 128 GB), Reset Button PoE, DC12V, IP67,3 axis adjustment Onvif support	۵۸۵۱۰۰۰۰



۴۸		<b><u>DS-2CD2152F-IS</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps, 4mm/F2.0 lens (6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, IK10, DC12V & PoE, DWDR, 3D DNR, BLC, support on-board storage up to 128GB(SD card not included), 3-axis adjustment, IR range: up to 30m, Vandal-proof housing, HIK-Connect cloud service -S: Audio/Alarm IO	۴۳۶۰۰۰۰۰
۴۹		<b><u>DS-2CD2352-I</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920:20fps, 4mm/F2.0 lens (2.8/6mm optional), H.264+/H.264/MJPEG, 3 streams, IP67, DC12V & PoE, DWDR, 3D DNR, BLC, EXIR range: up to 30m	۳۹۷۸۰۰۰۰
۵۰		<b><u>DS-2CD2955FWD-IS</u></b>	Up to 5 MP High Resolution Full 2560 × 1920 @30 fps H.265+, H.265, H.264+, H.264 14 Display Modes Supported Field of View: Horizontal 180°, Vertical 180° 120 dB Wide Dynamic Range 3D Digital Noise Reduction 12 VDC & PoE (802.3af) EXIR 2.0 with up to 30 ft (8 m) IR range MicroSD card slot supports up to 128 GB Audio and Alarm Inputs and Outputs	۱۰۵۷۸۰۰۰۰
۵۱		<b><u>DS-2CD2F52F-IS</u></b>	1/3" Progressive CMOS, ICR, 0lux with IR, 2560×1920: 20fps,2048×1536: 25fps(P)/ 30fps(N), 4mm/F2.0 lens (2.8/6mm lens optional), H.264+/H.264/MJPEG, 3 streams, DC12V & PoE, DWDR, 3D DNR, BLC, IR range: up to 10m, Support on-board storage up to 128GB(SD card not included), Pan: 0°~180°, Tilt: 0°~75°, HIK-Connect cloud service -S: Audio/Alarm IO	۲۹۶۵۲۰۰۰
۵۲		<b><u>DS-2CD2T43G0-IS</u></b>	4 MP IR Fixed Bullet Network Camera, 1/3" Progressive Scan CMOS, 2.8/4/6/8mm fixed lens, 2688 ×1520@30fps, Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264, 120dB WDR, BLC/3D DNR/ROI/HLC, IP67	۴۸۰۸۰۰۰۰
۵۳		<b><u>DS-2CD2T52-IS</u></b>	Up to 5 MP High Resolution λ Electronic Shutter λ Dual Video Streams λ Digital Wide Dynamic Range λ 3D Digital Noise Reduction λ 3-Axis Adjustment λ 12 VDC and PoE λ IR Cut Filter with Auto Switch λ 165 ft (50 m) EXIR Range λ IP67 Weather-Resistant Protection λ Mobile Monitoring via Hik-Connect or iVMS-4500	۳۹۵۰۴۰۰۰

تصویر	مدل	توضیحات	قیمت (ریال)
	<b><u>DS-2CD2123G0-IS</u></b>	1/2.8" Progressive Scan CMOS 1920 × 1080@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 Behavior analyses, and face detection BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	۴۰۷۱۰۰۰۰
	<b><u>DS-2CD2423G0-IW</u></b>	1920 × 1080@30fps IR: 10 m PIR: 10 m H.265+, H.265 120dB WDR Built-in MicroSD/SDHC/SDXC slot, up to 128G PoE EXIR Wi-Fi (Optional)	۳۳۹۲۰۰۰۰
	<b><u>DS-2CD2523G0-IS</u></b>	1920 × 1080@30fps IR: Up to 10 m H.265+, H.265 120dB WDR Built-in Micro SD/SDHC/SDXC slot, up to 128G PoE EXIR Wi-Fi (Optional)	۲۸۳۵۶۰۰۰
	<b><u>DS-2CD2723G0-IZS</u></b>	1/2.8" Progressive Scan CMOS 1920 × 1080@30fps 2.8 to 12 mm Varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 Three streams 120dB WDR 2 behavior analyses, and face detection BLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB 3-Axis adjustment	۵۱۴۲۰۰۰۰
	<b><u>DS-2CD1323G0E-I</u></b>	1/2.8" progressive scan CMOS 1920 × 1080@30fps 2.8 mm/4 mm fixed lens 3D DNR Up to 30 m IR range IP67 DWDR2 MP IR Fixed Network Turret Camera Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 Lux @ (F2.0, AGC ON)	۱۰۱۲۶۰۰۰



۵۹	 <p>DS-2CD1023G0E-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD1023G0E-I</u></b></p>	<p>1/2.8" progressive scan CMOS 1920 × 1080@30fps 2.8 mm/4 mm fixed lens 3D DNRUp to 30 m IR range IP67 ,DWDR,Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0, AGC ON) ,Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG</p>	۲۳۳۲۰۰۰۰
۶۰	 <p>DS-2CD2023G0-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD2023G0-I</u></b></p>	<p>1/2.8" Progressive Scan CMOS 1920 × 1080@30fps 2.8/4/6/8 mm fixed lens Color: 0.01 Lux @ (F1.2, AGC ON),0.028 Lux @ (F2.0, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 120dB WDR BLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot,up to 128 GB 2 MP IR Fixed Bullet</p>	۳۷۷۴۰۰۰۰
۶۱	 <p>DS-2CD2322WD-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD2322WD-I</u></b></p>	<p>2MP WDR EXIR Turret Network Camera,Full HD1080p video,2.8mm/4mm/6mm fixed lens,λ 120dB Wide Dynamic Range ,3D Digital Noise Reduction,DC12V &amp; PoE,Support H.264+,High performance EXIR LED,Up to 30m IR range,IP67,3-axis adjustment,0.01Lux @ (F1.2, AGC ON), 0 Lux with IR</p>	۳۷۷۴۰۰۰۰
۶۲	 <p>DS-2DE7184-AE <b>HIKVISION</b></p>	<p><b><u>DS-2DE7184-AE</u></b></p>	<p>2 MP Outdoor PTZ Dome Camera from Hikvision is equipped with a 1/2.8" progressive-scan CMOS sensor for up to 1920 x 1080 high-quality video resolution, and it uses a 4.7-94mm varifocal lens for a 58.3 to 3.2° horizontal field of view. 1920 x 1080 Video Resolution</p>	۱۵۵۱۳۰۰۰۰
۶۳	 <p>DS-2CD1323G0-I <b>HIKVISION</b></p>	<p><b><u>DS-2CD1323G0-I</u></b></p>	<p>2.0 MP IR Network Turret Camera,1/2.8" progressive scan CMOS,1920 × 1080@30fps,4 mm/6 mm fixed lens,H.265+, H.265, H.264+, H.264,WDR,3D DNR,Up to 30 m IR range,PoE,IP67,Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0, AGC ON)</p>	۱۴۰۶۴۰۰۰







**IP CAMERA 6MP**

تصویر	مدل	توضیحات	قیمت (ریال)
 <p>DS-2CD2063G0-I <b>HIKVISION</b></p>	<b><u>DS-2CD2063G0-I</u></b>	1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۲۶۷۱۲۰۰۰
 <p>DS-2CD2163G0-IS <b>HIKVISION</b></p>	<b><u>DS-2CD2163G0-IS</u></b>	1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۵۲۵۸۰۰۰۰
 <p>DS-2CD2563G0-IS <b>HIKVISION</b></p>	<b><u>DS-2CD2563G0-IS</u></b>	3072 × 2048@20fps IR: Up to 10 m H.265+. H.265 120dB WDR Built-in MicroSD/SDHC/SDXC slot, up to 128G PoE EXIR Wi-Fi (Optional)	۳۶۵۵۲۰۰۰
 <p>DS-2CD2663G0-IZS <b>HIKVISION</b></p>	<b><u>DS-2CD2663G0-IZS</u></b>	1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8 to 12 mm varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۶۵۴۸۴۰۰۰
 <p>DS-2CD2763G0-IZS <b>HIKVISION</b></p>	<b><u>DS-2CD2763G0-IZS</u></b>	1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8 to 12 mm varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۶۵۴۸۴۰۰۰


تصویر	مدل	توضیحات	قیمت (ریال)
<p>۶۹</p> 	<b><u>DS-2CD2T63G0-I5</u></b>	<p>1/2.9" Progressive Scan CMOS 3072 × 2048@20 fps 2.8/4/6/8 mm fixed lens                      Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses                      120dB WDRBLC/3D DNR/ROI IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	۵۵۱۲۰۰۰۰

IP CAMERA 4K

تصویر	مدل	توضیحات	قیمت (ریال)
<p>۷۰</p> 	<b><u>DS-2CD2083G0-I</u></b>	<p>1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	۵۶۸۲۰۰۰۰
<p>۷۱</p> 	<b><u>DS-2CD2183G0-IS</u></b>	<p>1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI/HLC IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB</p>	۶۱۹۱۰۰۰۰

۷۲		<b><u>DS-2CD2683G0-IZS</u></b>	1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8 to 12 mm vari-focal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI/HLC IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۷۵۷۶۸۰۰۰
۷۳		<b><u>DS-2CD2783G0-IZS</u></b>	1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8 to 12 mm varifocal lens Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI IP67, IK10 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۷۵۷۶۸۰۰۰
۷۴		<b><u>DS-2CD2T83G0-I5</u></b>	1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۴۲۲۱۶۰۰۰
۷۵		<b><u>DS-2CD2T83G0-I8</u></b>	1/2.5" Progressive Scan CMOS 3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR H.265+, H.265, H.264+, H.264 2 Behavior analyses 120dB WDRBLC/3D DNR/ROI/HLC IP67 Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	۶۹۵۴۰۰۰۰

**NVR 4 CHANEL**

تصویر	مدل	توضیحات	قیمت (ریال)
	<b><u>DS-7604NI-E1</u></b>	4-ch 1080P 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	۱۲۳۲۲۸۰۰

۷۷



**DS-7604NI-Q1**

4K (8 MP) HDMI Video Output @ 3840 × 2160 Resolution  
 H.265+/H.265/H.264/H.264+ Supports 4 IP Cameras Simultaneous HDMI/VGA Outputs 1 SATA Interface Supports Third-Party Network Cameras 1 Self-Adaptive 10/100/1000 Mbps Network Interface 4 Independent PoE Network Interfaces Long Distance (100 to 300 m) Network Transmission via PoE Hik-Connect for Easy Network Management

۳۰۵۱۰۰۰۰

۷۸



**DS-7104NI-Q1/4P/M**

04 CHANNEL H.265+ Mini 1U NVR Support 4 channel IP camera Support up to 4MP Resolution recording  
 H.265+,H.265,H.264+,H.264 video compression Max 40 Mbps Bit rate input Decoding Capability : 1-ch @ 4MP / 2-ch @ 1080p Playback 4 CH (4 CH@2Mp) 1 HDMI (1920\*1080 ), VGA Support 1 SATA (6TB), 2 USB 2.0,1 USB 3.0 RS-232, RS-485, 1 RJ45 (100) Mbps 4 POE Port ( 10/100 Mbps self-adaptive Ethernet interface) Support Onvif Version 2.0, Third-Party Network Camera

۳۲۷۵۰۰۰۰

۷۹



**DS-7108NI-Q1/M**

08 CHANNEL H.265+ Mini 1U NVR Support 8 channel IP camera Support up to 4MP Resolution recording  
 H.265+,H.265,H.264+,H.264 video compression Max 60 Mbps Bit rate input Decoding Capability : 1-ch @ 4MP / 2-ch @ 1080p Playback 8 CH (4 CH@2Mp) 1 HDMI (1920\*1080 ), VGA Support 1 SATA (6TB), 2 USB 2.0,1 USB 3.0 RS-232, RS-485, 1 RJ45 (100) Mbps Support Onvif Version 2.0, Third-Party Network Camera

۲۴۹۲۰۰۰۰

۸۰





**DS-7108NI-Q1/8P/M**

08 CHANNEL H.265+ Mini 1U NVR Support 8 channel IP camera Support up to 4MP Resolution recording  
 H.265+,H.265,H.264+,H.264 video compression Max 60 Mbps Bit rate input Decoding Capability : 1-ch @ 4MP / 2-ch @ 1080p Playback 8 CH (4 CH@2Mp) 1 HDMI (1920\*1080 ), VGA Support 1 SATA (6TB), 2 USB 2.0,1 USB 3.0 RS-232, RS-485, 1 RJ45 (100) Mbps 8 POE Port ( 10/100 Mbps self-adaptive Ethernet interface) Support Onvif Version 2.0, Third-Party Network Camera



۴۷۶۲۰۰۰۰





۸۱		<b><u>DS-7104NI-Q1/M</u></b>	04 CHANNEL H.265+ Mini 1U NVR Support 4 channel IP camera Support up to 4MP Resolution recording H.265+,H.265,H.264+,H.264 video compression Max 40 Mbps Bit rate input Decoding Capability : 1-ch @ 4MP / 2-ch @ 1080p Playback 4 CH (4 CH@2Mp) 1 HDMI (1920*1080 ), VGA Support 1 SATA (6TB), 2 USB 2.0,1 USB 3.0 RS-232, RS-485, 1 RJ45 (100) Mbps Support Onvif Version 2.0, Third-Party Network Camera	۱۹۸۳۰۰۰۰
۸۲		<b><u>DS-7604NI-K1</u></b>	1-ch 4K / 4-ch 1080P 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, standalone 1U case	۳۴۹۵۰۰۰۰






**NVR 8 CHANEL**

تصویر	مدل	توضیحات	قیمت (ریال)	
۸۳		<b><u>DS-7608NI-E2</u></b>	80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case	۳۸۰۱۰۰۰۰
۸۴		<b><u>DS-7608NI-K1</u></b>	8-ch,H.265/H.264/H.264+ video formats, Connectable to the third-party network cameras, Up to 16 IP cameras can be connected, Recording at up to 8 MP resolution, Supports live view, storage, and playback of the connected camera at up to 8 MP resolution, HDMI/VGA outputs provided, HDMI Video output at up to 4K (3840 × 2160) resolution	۳۷۳۷۰۰۰۰

۸۵		<b><u>DS-7608NI-Q1/8P</u></b>	08 CHANNEL H.265+ 1U NVR Support 8 Channel IP Camera up to 8 independent PoE Support up to 8MP Resolution recording H.265+,H.265,H.264+,H.264 video compression Max 80 Mbps Bit rate input Decoding Capability : 1CH@8MP, 4CH @ 1080P Playback 8 CH (4 CH@2Mp) 1 HDMI (4K ), VGA Support 1 SATA (8TB), 1 USB 2.0,1 USB 3.0 1/1 Audio I/O , 1 RJ45 (100) Mbps Support Onvif Version 2.0, Third-Party Network Camera	۳۱۱۳۵۰۰۰
۸۶		<b><u>DS-7608NI-Q1</u></b>	H.265+/H.265/H.264/H.264+ video formats λ Connectable to the third-party network cameras λ Up to 16 IP cameras can be connected λ Recording at up to 8 MP resolution λ Supports live view, storage, and playback of the connected camera at up to 8 MP resolution	۳۶۸۷۰۰۰۰
۸۷		<b><u>DS-7608NI-Q2</u></b>	H.265+/H.265/H.264/H.264+ video formats λ Connectable to the third-party network cameras λ Up to 16 IP cameras can be connected λ Recording at up to 8 MP resolution λ Supports live view, storage, and playback of the connected camera at up to 8 MP resolution	۲۱۱۵۵۰۰۰
۸۸		<b><u>DS-7608NI-K2</u></b>	2-ch 4K / 8-ch 1080P 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	۲۱۱۲۶۰۰۰

**NVR 16 CHANEL**

تصویر	مدل	توضیحات	قیمت (ریال)
-------	-----	---------	-------------

۸۹		<b><u>DS-7616NI-E2</u></b>	6-ch 1080P 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	۴۱۸۹۰۰۰۰
۹۰		<b><u>DS-7616NI-Q1</u></b>	H.265+/H.265/H.264/H.264+ video formats Connectable to the third-party network cameras Up to 16 IP cameras can be connected HDMI/VGA simultaneous output (DS-7604NI-Q1) HDMI and VGA independent outputs (DS-7608NI-Q1 and DS-7616NI-Q1) HDMI Video output at up to 4K (3840 × 2160) resolution 1 SATA interface connectable for recording and backup	۴۴۴۸۰۰۰۰
۹۱		<b><u>DS-7716NI-E4</u></b>	6-1080P 160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	۴۱۴۶۲۰۰۰
۹۲		<b><u>DS-7616NI-K2</u></b>	2-ch 4K / 8-ch 1080P 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1(optional)	۵۰۴۲۰۰۰۰
۹۳		<b><u>DS-7716NI-K4</u></b>	2-ch 4K / 8-ch 1080P 160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, alarm I/O: 16/4, 1.5U case,19"	۱۱۶۶۱۰۰۰۰

**NVR 32 CHANEL**

تصویر	مدل	توضیحات	قیمت (ریال)
-------	-----	---------	-------------

۹۴



**DS-7732NI-E4**

Third-party network cameras supported  
Up to 6 Megapixels resolution recording  
HDMI and VGA output at up to 1920×1080P resolution  
16/32-ch network cameras can be connected with 160M incoming bandwidth  
4 SATA interfaces Plug & Play with 16 independent PoE network interfaces  
Support network detection, including network delay, packet loss, etc

۵۴۳۷۳۰۰۰

۹۵



**DS-7732NI-K4**

Third-party network cameras supported  
Up to 8 Megapixels resolution recording  
Support 1-ch HDMI, 1-ch VGA, HMDI at up to 4K(3840x2160) resolution  
16/32-ch network cameras can be connected with 160M/256M incoming bandwidth  
Up to 4 SATA interfaces  
Support dual-os to ensure high reliability of system running  
Support various VCA detection alarm and VCA search  
Support H.265/H.264/MPEG4 video formats

۱۴۶۸۹۰۰۰۰

**NVR 4 CHANEL**

۹۶



**DS-7604NI-E1/4P**

4-ch 1080P  
40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case

۲۵۱۷۶۰۰۰

۹۷



**DS-7604NI-Q1/4P**

4K (8 MP) HDMI Video Output @ 3840 × 2160 Resolution  
H.265+/H.265/H.264/H.264+ Supports 4 IP Cameras Simultaneous HDMI/VGA Outputs  
1 SATA Interface Supports Third-Party Network Cameras  
1 Self-Adaptive 10/100/1000 Mbps Network Interface 4

۴۳۶۱۰۰۰۰





Independent PoE Network Interfaces - Long Distance (100 to 300 m) Network Transmission via PoE - Hik-Connect for Easy Network Management

۹۸



**DS-7604NI-K1/4P**

1-ch 4K / 4-ch 1080P  
40Mbps Bit Rate Input Max (up to 4-ch IP video)(Up to 300 meters), 1 SATA interfaces, 4 independent PoE network interfaces, standalone 1U case

۱۹۳۲۰۰۰۰

DS-7604NI-K1/4P  
**HIKVISION**

تصویر

مدل

توضیحات

قیمت (ریال)

۹۹



**DS-7604NI-Q1**



4K (8 MP) HDMI Video Output @ 3840 × 2160 Resolution  
 • H.265+/H.265/H.264/H.264+  
 • Supports 4 IP Cameras  
 • Simultaneous HDMI/VGA Outputs  
 • 1 SATA Interface  
 • Supports Third-Party Network Cameras  
 • 1 Self-Adaptive 10/100/1000 Mbps Network Interface  
 • 4 Independent PoE Network Interfaces  
 • Long Distance (100 to 300 m) Network Transmission via PoE  
 • Hik-Connect for Easy Network Management

۳۰۵۱۰۰۰۰



DS-7604NI-Q1  
**HIKVISION**







**NVR 8 CHANEL**

تصویر	مدل	توضیحات	قیمت (ریال)
<p>۱۰۰</p> 	<b><u>DS-7608NI-E2/8P</u></b>	<p>H.265+/H.265/H.264/H.264+ video formats Connectable to the third-party network cameras HDMI/VGA simultaneous output (DS-7604NI-Q1/4P) HDMI and VGA independent outputs(DS-7608NI-Q1/8P) HDMI Video output at up to 4K (3840 × 2160)resolution 1 SATA interface connectable for recording and backup H.265+ compression effectively reduces the storage space and costs by up to 75%</p>	۶۳۶۰۰۰۰۰
<p>۱۰۱</p> 	<b><u>DS-7608NI-K2/8P</u></b>	<p>2-ch 4K / 8-ch 1080P 80Mbps Bit Rate Input Max (up to 8-ch IP video)(Up to 300 meters), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)</p>	۴۷۷۸۴۰۰۰


تصویر	مدل	توضیحات	قیمت (ریال)
-------	-----	---------	-------------

۱۰۲	 	<p><b><u>DS-7608NI-E2</u></b></p>	<p>Up to 32-ch ONVIF conformant IP cameras input (max. incoming bandwidth: 160 Mbps)                  Live view of the connected camera at up to 6 MP resolution                  Compression and Recording                  H.264+ compression improves encoding efficiency by up to 50% and reduces data storage costs                  Full channel recording at up to 6 MP resolution                  Export with AVI format</p>	۳۸۰۱۰۰۰۰
-----	---	-----------------------------------	---	----------



**NVR 16 CHANEL WITH POE**



تصویر	مدل	توضیحات	قیمت (ریال)	
۱۰۳	 	<p><b><u>DS-7616NI-E2/8P</u></b></p>	<p>6-ch 1080P                  160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case</p>	۶۶۷۰۰۰۰۰
۱۰۴	 	<p><b><u>DS-7616NI-E2/16P</u></b></p>	<p>6-ch 1080P                  160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case</p>	۸۸۹۶۰۰۰۰

۱۰۵		<b><u>DS-7616NI-Q2/16P</u></b>	<p>third-party network cameras supported</p> <p>Supports live view, storage, and playback of the connected camera at up to 8 MP resolution</p> <p>Connectable to smart IP cameras from Hikvision and the recording, playing back, and backing up of VCA alarms can be realized</p> <p>VCA detection alarm is supported</p> <p>Hik-Connect for easy network management</p>	۹۴۸۰۰۰۰۰
۱۰۶		<b><u>DS-7616NI-K2/16P</u></b>	<p>2-ch 4K / 8-ch 1080P</p> <p>160Mbps Bit Rate Input Max (up to 16-ch IP video)(Up to 300 meters), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1(optional)</p>	۶۳۳۶۰۰۰۰
۱۰۷		<b><u>DS-7716NI-E4/16P</u></b>	<p>6-1080P</p> <p>160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"</p>	۶۲۲۲۷۰۰۰
۱۰۸		<b><u>DS-7716NI-K4/16P</u></b>	<p>2-ch 4K / 8-ch 1080P</p> <p>160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"</p>	۱۶۰۲۹۰۰۰۰



تصویر	مدل	توضیحات	قیمت (ریال)	
۱۰۹		<b><u>DS-7616NI-K2</u></b>	<p>H.265/ H.265+/H.264/H.264+/MPEG4 video formats</p> <p>Connectable to the third-party network cameras</p> <p>Up to 32 IP cameras can be connected</p> <p>Recording at up to 8 MP resolution</p> <p>Supports live view, storage, and playback of the connected camera at up to 8 MP resolution</p>	۵۰۴۲۰۰۰۰



۱۱۰	 	<p><b><u>DS-7616NI-Q2</u></b></p>	<p>Up to 16 channel IP cameras can be connected                  Supports decoding                  H.265+/H.265/H.264+/H.264 video formats                  Up to 4K high-definition live view, storage and playback                  Up to 4-ch @ 1080p decoding capacity                  Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected                  1 HDMI and 1 VGA interfaces: both interfaces support independent video output                  2 HDDs for continuous video recording                  Compatible with third-party network cameras</p>	۴۶۵۴۰۰۰۰
-----	--	-----------------------------------	--	----------





تصویر	مدل	توضیحات	قیمت (ریال)	
۱۱۱	 	<p><b><u>DS-7732NI-Q4-16P</u></b></p>	<p>H.265+/H.265/H.264/H.264+ video formats                  Connectable to the third-party network cameras                  Recording at up to 8 MP resolution                  HDMI Video output at up to 4K (3840 × 2160) resolution                  4 SATA interfaces connectable for recording and backup                  16 independent PoE network interfaces are provided                  playing back, and backing up of VCA alarms can be realized                  Instant playback for assigned channel during multi-channel display mode                  Smart search for the selected area in the video; and smart playback to improve the playback efficiency                  Hik-Connect for easy network management</p>	۱۷۷۹۶۰۰۰۰

تصویر	مدل	توضیحات	قیمت (ریال)
-------	-----	---------	-------------



۱۱۲	 	<p><b><u>DS-7716NI-Q4</u></b></p>	<p>Up to 16 channel IP cameras can be connected                  Supports decoding H.265+/H.265/H.264+/H.264 video formats                  Up to 4K high-definition live view, storage and playback                  Up to 4-ch @ 1080p decoding capacity                  Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected                  1 HDMI and 1 VGA interfaces: both interfaces support independent video output                  4 HDDs for continuous video recording                  Compatible with third-party network cameras</p>	۹۸۰۳۰۰۰۰
-----	--	-----------------------------------	---	----------

**NVR 32 CHANEL WITH POE**


تصویر	مدل	توضیحات	قیمت (ریال)	
۱۱۳	 	<p><b><u>DS-7732NI-K4/16P</u></b></p>	<p>2-ch 4K / 8-ch 1080P                  160Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"</p>	۱۸۸۴۲۰۰۰۰
۱۱۴	 	<p><b><u>DS-7732NI-E4/16P</u></b></p>	<p>6-1080P                  200Mbps Bit Rate Input Max(up to 32-ch IP video), 4 SATA Interfaces, 16 independent PoE network interfaces, alarm I/O: 16/4, 1.5U case,19"</p>	call

تصویر	مدل	توضیحات	قیمت (ریال)
 	<b><u>DS-7732NI-K4</u></b>	H.265/ H.265+/H.264/ H.264+/MPEG4 video formats, supports audio compressions Connectable to the third-party network cameras Up to 32 IP cameras can be connected Recording at up to 8 MP resolution Supports live view, storage, and playback of the connected camera at up to 8 MP resolution	۱۴۶۸۹۰۰۰۰
 	<b><u>DS-7732NI-Q4</u></b>	H.265+/H.265/H.264/H.264+ video formats Connectable to the third-party network cameras Up to 8/16/32-ch IP cameras can be connected for DS-7708/7716/7732NI-Q4 Recording at up to 8 MP resolution Live view, storage, and playback of the connected camera at up to 8 MP resolution	۱۲۱۳۰۰۰۰۰


**PTZ IP CAMERA**

تصویر	مدل	توضیحات	قیمت (ریال)
 	<b><u>DS-2DE4220IW-DE</u></b>	1/2.8" Progressive Scan CMOS 1920 x 1080 20X Optical Zoom DWDR 3D intelligent positioning function Support Hik-Connect Up to 100m IR distance 12VDC & POE(802.3at)	call



۱۱۸		<b><u>DS-2DE5220W-AE</u></b>	1/2.8" Progressive Scan CMOS Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR 3D intelligent positioning function Up to 150 m IR distance Hi-PoE/24 VAC power supply Support H.265 video compression	۲۳۷۷۷۰۰۰۰
۱۱۹		<b><u>DS-2DE5230W-AE</u></b>	1/2.8" Progressive Scan CMOS Up to 1920 × 1080 Resolution 30x Optical Zoom DWDR 3-D Intelligent Positioning IP66 / IK10 24 VAC / PoE (PoE Injector Included), 18 W	۱۶۱۲۶۸۰۰۰
۱۲۰		<b><u>DS-2DE7220W-AE</u></b>	1/2.8" Progressive Scan CMOS 1920 x 1080 20X Optical Zoom DWDR 3D intelligent positioning function Support cloud P2P Up to 150m IR distance Hi-PoE / 24VAC power supply	۱۶۲۳۴۸۰۰۰
۱۲۱		<b><u>DS-2DE7230W-AE</u></b>	1/2.8" Progressive Scan CMOS 1920 x 1080 30X Optical Zoom DWDR 3D intelligent positioning function Support EZVIZ cloud P2P Up to 150m IR distance Hi-PoE / 24VAC power supply	۱۸۷۷۸۸۰۰۰
۱۲۲		<b><u>DS-2DE7320W-AE</u></b>	1/2.8" Progressive Scan CMOS Up to 2048 × 1536 resolution 20× Optical Zoom, 16× Digital Zoom Digital WDR 3D intelligent positioning function Up to 150 m IR distance Hi-PoE/24 VAC power supply Support H.265 video compression	۲۸۴۳۲۰۰۰۰
۱۲۳		<b><u>DS-2DE4225W-DE</u></b>	1/2.8" progressive scan CMOS Up to 1920 × 1080@30fps resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 25× optical zoom, 16× digital zoom WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus Up to 100 m IR distance 12 VDC & PoE+ (802.3 at, class4) 2MP 25× Network IR Speed Dome	۱۴۸۸۱۰۰۰۰



۱۲۴		<p><b><u>DS-2DE7420IW-AE</u></b></p> <p>1/1.9" progressive scan CMOS Up to 2560 × 1536 resolution Min. illumination: Color: 0.005 Lux @(F1.5, AGC ON) B/W: 0.002 Lux @(F1.5, AGC ON) 0 Lux with IR 20× Optical Zoom, 16× Digital Zoom Defog, EIS, 3D DNR, BLC, HLC, Digital WDR IR distance up to 150 m 24 VAC &amp; Hi-PoE Support H.265+/H.265 video compression</p>	۲۲۵۱۲۰۰۰۰
-----	---	--	-----------

PTZ IP CAMERA			
تصویر	مدل	توضیحات	قیمت (ریال)
۱۲۵		<p><b><u>DS-2DE7430IW-AE</u></b></p> <p>1/1.9" progressive scan CMOS Up to 2560 × 1440 resolution Min. illumination: Color: 0.005 Lux @(F1.5, AGC ON) B/W: 0.002 Lux @(F1.5, AGC ON) 0 Lux with IR 30× Optical Zoom, 16× Digital Zoom Defog, EIS, 3D DNR, BLC, HLC, Digital WDR IR distance up to 150 m 24 VAC &amp; Hi-PoE Support H.265+/H.265 video compression</p>	۲۴۶۲۲۸۰۰۰
۱۲۶		<p><b><u>DS-2DE7530IW-AE</u></b></p> <p>1/1.9" progressive scan CMOS Up to 2592 × 1944 resolution Min. illumination: Color: 0.005 Lux @(F1.5, AGC ON) B/W: 0.002 Lux @(F1.5, AGC ON) 0 Lux with IR 30× Optical Zoom, 16× Digital Zoom Defog, EIS, 3D DNR, BLC, HLC, Digital WDR IR distance up to 150 m 24 VAC &amp; Hi-PoE Support H.265+/H.265 video compression</p>	۲۷۷۰۵۶۰۰۰
۱۲۷		<p><b><u>DS-2DE2202I-DE3</u></b></p> <p>2 MP High Resolution Compact IR Pan/Tilt/Zoom Camera 1920 x 1080p HD Real-Time Resolution 2x Zoom, 16x Digital Zoom 20 Meters IR Distance PoE and 12 VDC Power Supply Built-In Mic, WiFi MicroSD Card Local Storage, Up to 128 GB Easy To Install and Adjust</p>	۳۱۶۸۰۰۰۰
۱۲۸		<p><b><u>DS-2DE4A220IW-DE</u></b></p> <p>1/2.8" Progressive Scan CMOS Up to 1920 × 1080 resolution 20× Optical Zoom, 16× Digital Zoom WDR, 3D DNR, HLC, Smart IR Up to 50 m IR distance 12 VDC &amp; PoE+ (802.3at, class4) Support H.265 video compression</p>	۸۴۱۳۲۰۰۰

۱۲۹

**DS-2PT3326IZ-DE3**

1/2.8" progressive scan CMOS  
 3-ch1920 × 1080@30fps resolution  
 Min. illumination:  
 Color: 0.05 Lux @(F2.0, AGC ON)  
 B/W: 0.01 Lux @(F2.0, AGC ON)  
 0 Lux with IR  
 Support H.265 video compression  
 Horizontal FOV: 128.5° × 3  
 PTZ Camera  
 1/2.8" progressive scan CMOS  
 Up to 1920 × 1080@30fps resolution  
 Min. illumination:  
 Color: 0.05 Lux @(F2.0, AGC ON)  
 B/W: 0.01 Lux @(F2.0, AGC ON) 0 Lux with IR  
 Support H.265 video compression  
 4× optical zoom, 8× digital zoom

۱۵۲۹۲۰۰۰۰

**برای دریافت لیست قیمت به روز کلیه  
 محصولات امنیتی و دریافت تخفیفات ویژه  
 همکاران و مشتریان روی لینک زیر کلیک  
 کنید.**



# HIKPERSIAN.IR

