


## DS-2CD2632F-I 3.0 MP VF IR Bullet Network Camera



### Key Features

- Up to 3 Megapixel (2048 x 1536) Resolution
- Full HD1080p Real-Time Video
- Varifocal Lens
- IR LEDs Up to 30 Meters Range
- DWDR, 3D DNR, and BLC
- IP66
- Supports On-Board Storage Up to 128 GB

### Dimensions



### Order Models

DS-2CD2632F-I

DS-2CD2632F-I	
<b>Camera</b>	
Image Sensor	1/3" progressive scan CMOS
Minimum Illumination	0.095 lux @ f/1.4 0 lux with IR
Shutter Speed	1/30 s to 1/100,000 s
Lens	2.8 mm to 12 mm @ f/1.4, angle of view: 98° to 30.5°
Lens Mount	Φ14
Day/Night	ICR
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Backlight Compensation	Yes, zone configurable
<b>Compression Standard</b>	
Video Compression	H.264/MJPEG
H.264 Compression Profile	Main Profile
Bit rate	32 Kbps to 16 Mbps
<b>Image</b>	
Maximum Image Resolution	2048 × 1536
Frame Rate	60 Hz: 15 fps (2048 x 1536), 30 fps (1920 × 1080), 30 fps (1280 x 720)
Image Settings	Saturation, brightness, contrast adjustable through client software or Web browser
<b>Network</b>	
Network Storage	NAS
Alarm Triggers	Motion detection, tampering alarm, network disconnect, IP address conflict, storage full, storage error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1X, QoS, HTTPS
System Compatibility	ONVIF, PSIA, CGI, ISAPI
General Functionalities	User authentication, watermark, dual stream
<b>Interface</b>	
Communication Interface	1 RJ-45 10M/100M Ethernet port
On-Board Storage	Built-in microSD/SDHC/SDXC card slot, up to 128 GB
<b>General</b>	
Operating Conditions	-30° C to 60° C (-22° F to 140° F), humidity 95% or less (non-condensing)
Power	12 VDC ±10%, PoE (802.3af)
Power Consumption	Maximum 5.5 W (7.5 W with ICR on)
Ingress Protection Level	IP66
IR Range	Up to 30 meters
Dimensions	95 mm x 105 mm x 258.6 mm (3.74" x 4.13" x 10.18")
Weight	1200 g