





	<b>DS-1005KI</b>	Full-featured USB keyboard Supports various cameras, NVRs, DVRs and also iVMS 4200 Flexible 4-axis joystick Buttons can be used to perform powerful functions	CALL	1
	<b>DS-1100KI</b>	<ul style="list-style-type: none"> <li>• 7" TFT touch screen at 800×480 resolution</li> <li>• Speed dome, video decoder &amp; DVR control</li> <li>• 1-ch HD video stream decoding at 1080p</li> <li>• Support 15 users, and each can operate up to 256 devices</li> <li>• USB 2.0 interface for video backup</li> </ul>	CALL	2
	<b>DS-1602ZJ</b>	Wall Mount Aluminum alloy Hikvision White	CALL	3
	<b>DS-1661ZJ</b>	Pendent Mount Aluminum Alloy Hikvision White	CALL	4
	<b>DS-1662ZJ</b>	Pendent Mount (50cm) Aluminum Alloy Hikvision White	CALL	5


	<p><b>DS-1681ZJ</b></p>	<p>Colour: White Size : 176.8*194*419.5mm Weight:1 kg Material: Aluminium Alloy</p>	<p>Call</p>	<p>6</p>
	<p><b>DS-1LN6-UE-W</b></p>	<p>305 m CAT6 UTP Network Cable (Solid Copper, 0.53 mm, CM) Full diameter 305 m CAT6 network cable Core diameter: 0.53mm Excellent transmission performance using solid copper Quality verified by Fluke test Guaranteed long PoE transmission distance Great PVC flame resistance</p>	<p>CALL</p>	<p>7</p>
	<p><b>DS-1LN6-UU</b></p>	<p>305 m CAT6 UTP Network Cable (Solid Copper, 0.565 mm, CM) Popular Full diameter 305 m CAT6 network cable Core diameter: 0.565mm Excellent transmission performance using solid copper Quality verified by Fluke test Guaranteed long PoE transmission distance Great PVC flame resistance.</p>	<p>CALL</p>	<p>8</p>
	<p><b>DS-TT-X41T-tester</b></p>	<p>TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs 7" TFT active matrix LCD monitor TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps</p>	<p>Call</p>	<p>9</p>



	<p><b>DS-2AE4225TI-D</b></p>	<p>High quality imaging with 2 MP resolution          Excellent low-light performance via powered-by-DarkFighter technology          Clear imaging against strong back lighting due to 120 dB WDR technology          Pan and tilt ability enables camera to monitor zones of interest          25 × optical zoom allows for closer viewing of subjects in expansive areas          Up to 100 m IR range ensures safety at night          Water and dust resistant (IP66)</p>	<p>CALL</p>	<p>10</p>
	<p><b>DS-2DE4225IW-DE-T5</b></p>	<p>Accurate human and vehicle target classification and alarm based on deep learning algorithm          Support face capture. Up to 5 faces captured at the same time          1/2.8" Progressive Scan CMOS          Up to 1920 × 1080@30fps          Min. illumination: Color: 0.005Lux @ (F1.6, AGC ON), B/W: 0.001Lux @ (F1.6, AGC ON), 0 Lux with IR          25×optical zoom, 16× digital zoom          WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus          Up to 100m IR distance          12VDC &amp; POE(802.3at)          Support H.265+/H.265</p>	<p>124,900,000</p>	<p>11</p>



	<p><b>DS-2DE4425IW-DE-T5</b></p>	<p>High quality imaging with 4 MP resolution          Excellent low-light performance via powered-by-DarkFighter technology          Clear imaging against strong back lighting due to 120 dB WDR technology          Pan and tilt ability enables camera to monitor zones of interest          25x optical zoom allows for closer viewing of subjects in expansive areas          Up to 100m IR range ensures safety at night          Water and dust resistant (IP66)</p>	<p>145,870,000</p>	<p>12</p>
	<p><b>DS-2DE5432IW-AE</b></p>	<p>1/2.8" Progressive Scan CMOS          High quality imaging with 4 MP resolution          Excellent low-light performance with powered-by-DarkFighter technology          32x optical zoom, 16x digital zoom          WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus          Up to 150 m IR distance          Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm          Face capture: Up to 5 faces captured at the same time</p>	<p>229,050,000</p>	<p>13</p>

	<p><b>DS-2DE7232IW-AE</b></p>	<p>High quality imaging with 2 MP resolution          Excellent low-light performance via powered-by-DarkFighter technology          Clear imaging against strong back lighting due to 120 dB WDR technology          Pan and tilt ability enables camera to monitor zones of interest          32x optical zoom allows for closer viewing of subjects in expansive areas          Up to 150m IR range ensures safety at night          Water and dust resistant (IP66).</p>	<p>Call</p>	<p>14</p>
-----------------------------------------------------------------------------------	-------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------	-----------

